Channel body ACO ShowerDrain C, Horizontal Flange, Horizontal lateral outlet

Product information for the product group

ACO Product benefits

- Minimum installation height
- Meets requirements of all sound protection levels (SSt I-III in acc. with VDI 4100)
- Free access to the pipe for optimal cleaning
- Factory-welded hydro-shaped gully, guarantees permanent tightness
- Removable foul air trap for optimal cleaning
- High drainage capacity





- Material: Stainless steel, material grade 304
- Load class: K3
- Internal channel width: 64 mm
- Installation height: 92-140 mm (incl. 12 mm frame height)
- Flow rate:
  - 0.72 l/s (WS50 with 10 mm build-up)
  - 0.91 l/s (WS50 with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket version: ND 50
- Foul air trap: 2-part, removable
- Type of flange: surrounding flange
- Channel body: Pickle passivated
- Mounting: Ready for installation
- Sound protection (as standard)
- Height adjustability: 48 respectively 74 mm using height-adjustable feet (to be ordered as an accessory)
- Grating variants: Stainless steel design gratings, tileable cover
- Supplementary components: ACO ShowerStep and ACO EasyStop

For more information please visit:
https://www.aco.co.uk/ShowerDrainC

Excluding errors and changes.

Item Technical Data



Part No	Description	Odour trap	Dimensions		
			L1	L2	Overall Width
			[mm]	[mm]	[mm]
2131534	Surrounding flange, socket horizontal/lateral	With	585	645	130
2131535	Surrounding flange, socket horizontal/lateral	With	685	745	130
2131536	Surrounding flange, socket horizontal/lateral	With	785	845	130
2131537	Surrounding flange, socket horizontal/lateral	With	885	945	130
2131538	Surrounding flange, socket horizontal/lateral	With	985	1045	130
2131539	Surrounding flange, socket horizontal/lateral	With	1085	1145	130
2131540	Surrounding flange, socket horizontal/lateral	With	1185	1245	130

For more information please visit:
https://www.aco.co.uk/ShowerDrainC

Excluding errors and changes.