

www.akirby.co.uk

TECHNICAL INFORMATION SHEET

900106 Westray Oak Caledonian Collection



Product Details

Surface	Brushed
Finish	UV Oil
Grade	Super Rustic
Profile	5G
Edge	Bevelled
Pattern	Plank
Width	190mm
Length	1900mm
Thickness	14mm
Wear Layer	3mm
Backing	Poplar
Top Layer	Oak
Grading Information	

Super Rustic grade is likely to contain all characteristics across all boards with any size of knot and level of colour variation in the timber to be expected. Expect to see some sapwood as well as checks and filler used in a colour to complement these natural variances in most boards.

Product Information

Product Name Product Code Collection Construction Size Pack Size Grade Westray Oak 900106 Caledonian Engineered 14 x 190 x 1900mm 2.89 Super Rustic

Installation Method

Floated	Yes
Secret Nailed	No
Stuck Down	Yes
Underfloor Heating	Yes

Technical Information

Formaldehyde Emissions Pentachlorophenol Emissions	E1 Not Detectable
Hardness Rating	3.7
Fire Classification	Dfl-s1
Thermal Conductivity	0.14W/mK
Moisture Content	7-10%
Responsible Certification	Please ask a member of the team

Installation and Warranty

Atkinson & Kirby recommend all floors should be installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions found on our website.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice to third parties. To confirm the latest information, please speak to a member of the team



Atkinson & Kirby, Archwood House, Kingsfield Court, Chester, CH4 9RE T: 01695 573234 | E: sales@akirby.co.uk