

breathAplasta™

Performance
Plaster.
Made Easy.



Fast setting and easy
to use. Saving you
time on installation.



Breathable -
water vapour
permeable.



Proven to reduce
condensation
and mould.



UKCA and CE
marked with
A1 fire rating.

thermal

Insulate solid walls



Highly
insulative
thermal base
layer.

COVERAGE:
2m² at 10mm
THICKNESS

universal

Improve air quality



Breathable
bio-based
formulation.

COVERAGE:
5m² at 4mm
THICKNESS

smooth

Smooth surface finish



High quality
smooth surface
finish.

COVERAGE:
12m² at 3mm
THICKNESS



Adaptavate



See
more
here



System Guide Checklist

breathAplasta
thermal | universal | smooth



Mist
background

Mesh

Primer

Aftercare
Mist first 1-2 days
after installation

Internal Wall Insulation (IWI)
Masonry: Brick, Block and Stone



Internal Wall Insulation (IWI)
Wood fibre board



Over skimming/overcoating



Plasterboard



Performance plasterboard
(Acoustic, fire & moisture resistant)



Lath and plaster



Wood wool boards



Hempcrete



Masonry levelling coat
(brick, block and stone)



Levelling coat onto masonry (optional)

Can apply onto surface

Apply as finishing coat onto Thermal and Universal only

Optional

Not applicable