

# ARUNDEL BUFF MULTI

## CBP-ABC-ARU

### TEXTURE, TYPE & COLOUR

Handmade facing bricks for interior and exterior use in decorative or construction walls.

Arundel Buff Multi from the ABC Klinker factory. A gentle buff coloured soft mud facing brick with a warm autumnal feel. With the handmade texture, variations of light and dark shading adds a sense of depth to this lovely sanded brick.

### TECHNICAL CHARACTERISTICS

The facing bricks are delivered with the following characteristics, in accordance with the CE and Benor marks:

NEN-EN 771-1, April 2013, and NEN-EN 771-1/A1, March 2005 Category I, HD clay bricks.

### NOTE

Dimensions may vary depending on the production. For the most recent version see [www.camtechbp.co.uk](http://www.camtechbp.co.uk). This document is not binding and annuls all previous publications. The manufacturer reserves the right to change the product range and characteristics. The user must always check that they have the most recent descriptive text.



FACTORY: ABC KLINKER



NEN-EN 771-1, April 2013, and NEN-EN 771-1/A1, March 2005 Category I, HD clay bricks  
Production Reference code: ABC Klinker KHLZB 28-1,6 - BS Gelb

Length	: 215 mm, T2 (+/- 4 mm), R1 (9 mm)
Width	: 102 mm, T2 (+/- 3 mm), R1 (6 mm)
Thickness	: 65mm, T2 (+/- 2 mm), R1 (5 mm)
Appearance	: Perforated Wirecut, Euro group 1
Average compressive strength	: >35 N/mm <sup>2</sup>
Dimensional stability	: NPD
Bond strength	: NPD
Active soluble salts	: S2
Reaction to fire	: Euro class A1
Water absorption	: <6% m/md
Water vapour diffusion coefficient	: 50/100
Gross dry density	: 1600 kg/m <sup>3</sup> , D1 (10%, +/- 160 kg/m <sup>3</sup> )
Thermal conductivity	: NPD - EN 1745;2012
Freeze/thaw resistance	: F2

ASK FOR  
SAMPLES

Call Camtech: 01763 262006



We want to help you make informed decisions and find the right solution for your business, customers or project; after all, it's much more than just a product, Right!



**CAMTECH BUILDING PRODUCTS LTD**  
p. Camtech House, 21 Jarman Way  
Royston, Herts, SG8 5HW. UK

t. +44 (0)1763 262006  
e. [info@camtechbp.co.uk](mailto:info@camtechbp.co.uk)  
w. [camtechbp.co.uk](http://camtechbp.co.uk)