



TECHNICAL DATA SHEET

Cromaslate

Description:

Cromaslate offers a Great Alternative to Natural Slate.

Benefits:

- Lightweight
- Easy fixing
- 5mm spacer
- 40 years life expectancy
- 100% Recyclable
- BS476 Part 3 Fire rating EXT.S.AC
- BRE Wind and Rain to EN15601.
- Textured finish for the natural slate look.
- Easy to cut with fine tooth hand saw
- No Grading
- No Drilling

Application:

- Conservatories
- Pitched roofs
- Lean to roofs
- Minimum pitch 15°
- Maximum Pitch 90°

Typical Properties:

- Recycled Polypropylene with UV.

Storage:

- Minimum 7 degrees
- Fixing 0 degrees

Technical Data:

- Maximum gauge 200 mm
- Minimum Pitch 15°
- Maximum Pitch 90°
- Slate Size 425mm x 330mm
- Weight per slate 650 grams
- Packaged in bundles of 15 (1m²)
- Bundle weight 9.75 kg
- Bundles per pallet 54
- Pallet quantities 810 Slates
- Pallet Weight 534 kg

Colours Available:

- Slate Grey



Fixings:

- Corrosive resistant 30mm large head ring shank nails or screws
- 25 x 50mm battens
- 18mm Plywood/OSB

Associated Products:

- Cromar Vent 3 membrane
- Cromar Eaves ventilation
- Cromar Pro dry ridge system.
- Ridge tiles

Newly designed ridge tiles that are manufactured with the Cromaslate to match with texture and colours , with a 225mm visible face. Size 300mm x 490mm

- Ridge Tile System 2

The ridge tile system 2 provides an attractive uniform alternative finish to the standard ridge giving customer choice and satisfaction. Come with it's own end ridge caps. With a colour match of the slates. Size: 330mm x 170mm

- Hip ridge and end cap.

Attractive angle ridge for the hip to match the ridge tile 2 system and the hip end cap provides the perfect finish at the base of the hip.

- 3 Way Ridge to Hip Cap.

For a professional finish where 2 hips meet with the main ridge for the perfect mitre joint.

- Caps for screws

Designed to cover screw holes in the ridge tile system 2 to create a flush finish. Colour match for the slates.