



Declaration of Performance				
1	Commercial name of the product	Polperro Natural Slate™		
2	Quarry location:	Ourense, Spain		
3	Product Description:	Slate for roofing and exterior cladding		
	Format:	50x25 - 40x25 - 40x20 - 30x20		
4	Name, registered trade name or registered trade marks and contact address of the manufacturer as required under Article 11(5):	Westcountry Slate Supplies Ltd, 3 Budlake Road, Marsh Barton, Exeter EX2 8PY		
5	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	N/A		
6	System or systems of assessment and vertification of constancy of performance of the construction product as set out in CPR, Annex V:	System 4		
7	Dimensional Tolerances			
	Deviation from declared length (mm):	< ± 3mm	UNE EN 12326-1(1)	
	Deviation from declared width (mm):	< ± 3mm	UNE EN 12326-1 ⁽¹⁾	
	Deviation from squareness (%):	< ±1%	UNE EN 12326-1 ⁽¹⁾	
	Deviation from straightness of edges (%)	<5mms & <± 1% length	UNE EN 12326-1(1)	
	Deviation from flatness:	< 1.0%	UNE EN 12326-1 ⁽¹⁾	
	Thickness			
	Nominal thickness and variation:	6.5mm±35%	UNE EN 12326-1(1)	
	Strength			
	Characteristic MoR:	Longitudinal: 38.4 N/mm2	UNE EN 12326-1 ⁽¹⁾	
		Traverse: 37.7 N/mm2	UNE EN 12326-1 ⁽¹⁾	
	Water absorption:	(<0.6%) Class W1	UNE EN 12326-1(1)	
	Freeze and thaw:	Not Required		
	Thermal cycle:	T1	UNE EN 12326-1(1)	
	Carbonate content:	0.4%	UNE EN 12326-1(1)	
	Sulphur dioxide exposure test:	S1	UNE EN 12326-1(1)	
	Non-carbonate carbon content:	0.4%	UNE EN 12326-1 ⁽¹⁾	
	Exposure to external fire:	Class Broof		
	Reaction to fire:	It is considered to Comply with A1 Class		
	Release of dangerous substances:	None in Normal Conditions of use as Roofing or Cladding	UNE EN 12326-1 ⁽¹⁾	

⁽¹⁾The tests referred to and the criteria are included in the UNE EN-12326-1:2015 and 2:2012 Standards.

Signed for and on behalf of the manufacturer by:

Darren Shields, Managing Director **Date of Issue:** 08/01/2024

^{8.} Performance of the product identified in Points 1 and 2 is in conformity with the declared performance in point 7.

^{9.} This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.