

## Product Safety Information

Although the REACH Regulation does not require a Safety Data Sheet to be provided for EcoTherm products, as they are considered articles under the Regulation, this Product Safety Information Sheet has been prepared to reflect the primary SDS requirements as set out in Annex II to Regulation (EC) No 1907/2006 (REACH), as amended at the date of the publication, as they might reasonably apply to articles.

### 1. Identification of the product and of the company / undertaking

#### 1.1 Product identifier

Eco-Versal  
Eco-Cavity  
Eco-Cavity Full Fill  
Eco-Liner  
Eco-Fix  
Eco-Bond  
Eco-Torch  
Eco-Fix Tapered  
Eco-Bond Tapered  
Eco-Torch Tapered

#### 1.2 Relevant identified uses of the product

Rigid thermoset polyurethane (PUR) or polyisocyanurate (PIR) insulation for building fabric and building services applications. No uses advised against on physical, health or environmental grounds based on the provisions of the REACH Regulation.

#### 1.3 Details of the supplier of the Product Safety Information Sheet

Company Name: Kingspan Insulation Ltd.  
Address: Pembridge, Leominster,  
Herefordshire HR6 9LA.  
Tel: +44 (0) 1268 591 155  
Email: [ecotherminfo@kingspan.com](mailto:ecotherminfo@kingspan.com)  
Website: [www.ecotherm.co.uk](http://www.ecotherm.co.uk)

#### 1.4 Technical Support contact details

Tel: +44 (0) 1268 591 155  
Email: [ecothermtechnical@kingspan.com](mailto:ecothermtechnical@kingspan.com)

### 2. Hazards identification

#### 2.1 Classification

There are no applicable Globally Harmonised System (GHS) hazard statements for the substances contained in these products. Accordingly, there are no known hazards associated with the normal handling or use of these insulation products.

#### 2.2 Label elements

In line with the lack of classification, there are no specific labelling requirements.

#### 2.3 Other hazards

Cutting and sanding may generate dust. As with most types of nuisance dust, excessive dust may irritate the eyes, respiratory tract or sensitive skin. See Section 8.1 for further information.

### 3. Composition information

3.1 Core:	Rigid thermoset urethane (PUR or PIR as defined by EN 13165 : 2012 + A2: 2016) insulation.
Alternative facings:	Aluminium composite foil (Eco-Versal, Eco-Cavity, Eco-Cavity Full Fill, Eco-Fix). Bitumen coated glass tissue (Eco-Torch). Coated glass tissue (Eco-Bond, Eco-Torch). Bilaminate foil/kraft paper facing and 12.5mm tapered edge gypsum plasterboard (Eco-Liner).

#### 3.2 Tapered versions

Eco-Fix Tapered  
Eco-Bond Tapered  
Eco-Torch Tapered

Further information on facings available upon request.

## 4. First aid measures

### 4.1 Description of first aid measures

Inhalation:	Remove the person to fresh air.
Skin:	Wash carefully using soap and water or a proprietary cleanser to remove.
Eyes:	Dust particles should be removed by flushing with clean water.
Ingestion:	Drink plenty of water if dust particles are accidentally ingested.

### 4.2 Most important symptoms and effects, both acute and delayed

Inhalation:	Dust is non-hazardous. Possible irritation or soreness in throat and nose.
Skin:	Temporary irritation or rash. Nonsensitising. When facings containing glass fibres are handled, skin irritation may occur.
Eyes:	Temporary irritation or inflammation.
Ingestion:	No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if needed. Treat symptomatically.

## 5. Firefighting measures

### 5.1 Extinguishing media

Suitable media:	Water spray (fog), foam, CO <sub>2</sub> or dry chemical.
Unsuitable media:	Not applicable.

### 5.2 Special hazards arising from the product

It is prudent to take precautions against ignition, fire spread and combustion products. As with all organic products, PIR will combust under severe fire conditions, where various oxides of carbon may form. There are no brominated flame retardants present in these products. Do not incinerate waste foam in an open environment.

Do not inhale fumes; fire fighters should attack the fire according to the combustible materials present and use breathing apparatus. Cardboard and plastic packaging materials are combustible. Store away from all possible sources of ignition.

### 5.3 Advice for firefighters

Firefighters should use self-contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid / minimise the creation of airborne dust. In the event of high dust levels, use approved respiratory protective equipment (see Section 8).

### 6.2 Environmental precautions

Do not release collected dust to drains or waterways (see Section 13 for Disposal considerations).

### 6.3 Methods and material for containment and cleaning up

Prevent excessive dust generation and use dust sheets before cutting to capture any dust generated. If dust does accumulate use vacuum cleaner or dampen with water spray to prior to sweeping up.

### 6.4 Reference to other sections

See Section 8 for PPE.

See Section 13 for Disposal considerations.

## 7. Handling and storage

### 7.1 Precautions for safe handling

As with all cutting procedures it is recommended that a disposable dust mask be worn. Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used. If dust generation persists over a sustained period in an enclosed space, the level of dust should be monitored in line with local regulations.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in original packing in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat. Traces of ethanol may be released from material that is freshly produced.

Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.

## 8. Exposure controls / personal protection

### 8.1 Control parameters

There are no specific occupational exposure limits (OELs) for PUR or PIR dust itself, but best practice is not to exceed 3 mg/m<sup>3</sup> based on an 8-hour time-weighted average (TWA).

### 8.2 Exposure controls

Inhalation:	Dust is non-hazardous. Dust from timber facings may cause respiratory irritation.  As with all cutting procedures it is recommended that a disposable dust mask be worn.  Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used.
Hands:	It is recommended that gloves be worn when handling the products.
Eyes:	Eye protection recommended during mechanical cutting. When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
Skin:	Non-sensitising. It is recommended to wear gloves when handling the products. When installing a product with reflective facings in bright sunlight, it is advisable to consider skin protection from UV.
Other:	The products are non-load bearing. Access and work should not be carried out on unsupported boards.  The smooth facing used on some EcoTherm products can be slippery underfoot when wet.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Yellow foam with composite foil, glass reinforced perforated cellulose, glass tissue, bitumen coated glass tissue, coated glass tissue, WBP exterior grade plywood or PVC facings.
Odour:	Negligible.
pH:	Neutral under normal conditions.
Melting point:	Not applicable.
Flash point:	Not applicable.
Solubility in water:	Insoluble.
Solubility in organics:	Some liquids may cause swelling.
Other data:	None.

### 9.2 Other information

No additional chemical or physical properties to report.

## 10. Stability and reactivity

### 10.1 Reactivity

Unreactive during normal use (see Section 7).

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Not reactive.

### 10.4 Conditions to avoid

None specified.

### 10.5 Incompatible materials

None specified.

### 10.6 Hazardous decomposition products

None specified.

## 11. Toxicological information

### 11.1 Information on toxicological effects

There are no known adverse health effects arising from handling or using EcoTherm insulation as supplied.

### 11.2 Information on other hazards

No additional information available.

## 12. Ecological information

### 12.1 Toxicity

The products are chemically inert and stable in water and soil.

### 12.2 Persistence and degradability

PIR is not biodegradable and in common with most polymer materials will be persistent in the environment because of its durability.

### 12.3 Bio-accumulative potential

None anticipated since the product is a chemically inert polymeric matrix.

### 12.4 Mobility in soil

No anticipated mobility.

### 12.5 Results of PBT and vPvB assessment

Testing inappropriate for articles.

### 12.6 Endocrine disrupting properties

No data available.

### 12.7 Other adverse effects

Blowing agents used in the EcoTherm range of products have negligible Ozone Depletion Potential (ODP) and low Global Warming Potential (GWP).

## 13. Disposal considerations

### 13.1 Waste treatment methods

Waste insulation is considered to be non-hazardous. Waste created in the production process is compacted in the form of a briquette. It is chemically inert and disposed of in line with the precautions set out in Sections 7 and 8.

NB: The briquette dimensions approx. 160 x 130 x 70 mm, and density of approx. 500-550 kg/m<sup>3</sup>.

Product dust created in the installation process is regarded as nuisance dust only, because of its chemically inert nature, but it is good practice to minimise dust generation and dispose of it responsibly in line with the precautions set out in Sections 7 and 8. Clean, undamaged product may be re-used.

Waste product, including packaging, should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle. Refer to national waste handling legislation.

With respect to disposal, observe usual safety precautions with polythene bags, wrapping and packaging.

## 14. Transport information

Read this section in conjunction with Section 7.

Ensure security of load and where necessary sheeting /roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the product

Since polyurethane and polyisocyanurate foams covered by this Product Safety Information sheet are not identified as hazardous waste under the Waste

Framework Directive (EU 851/2018) and do not contain substances that display hazardous endpoints under

GHS or are classified under CLP (EC 1272/2008), there are no regulations currently applicable to EcoTherm.

### 15.2 Chemical safety assessment

No assessment required.

## 16. Other information

The information contained here is offered in good faith and is based on our current knowledge.

We thereby maintain the right to update and amend this document as necessary.

The information should not be taken as a guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application. Please refer to Sections 7 and 8 for safe handling and appropriate safety measures.

Users should visit the Ecotherm Insulation website or contact the Ecotherm Insulation Technical Service Department to ensure information is current.

This data sheet does not constitute a workplace assessment. The information provided represents the state of our knowledge regarding this material at the date of its publication. The information provided does not constitute a product specification and no warranty expressed or implied is hereby made.

The information relates only to the specific material designated when used in applications it has been designed for. This information may not be valid for such material used in combination with any other materials or in any other processes, unless specified in the text.

## Contact details

**Kingspan Insulation Ltd.**

Pembridge, Leominster,  
Herefordshire HR6 9LA.

Tel: +44 (0) 1268 591 155

Email: [ecotherminfo@kingspan.com](mailto:ecotherminfo@kingspan.com)

[www.ecotherm.co.uk](http://www.ecotherm.co.uk)

**EcoTherm Technical Services:**

[ecothermtechnical@kingspan.com](mailto:ecothermtechnical@kingspan.com)



For the most up-to-date version of this product safety sheet please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk).

The information contained in this brochure is believed to be correct at the date of publication. Kingspan Insulation Limited, trading as EcoTherm Insulation, reserves the right to alter or amend the product specifications without notice due to continuous improvement commitments. There may also be relevant changes between publications with regard to legislation, or other developments affecting the accuracy of the information contained in this brochure.

Product thicknesses shown in this document should not be taken as being available ex-stock and reference should be made to the current EcoTherm Insulation price-list or advice sought from Kingspan Insulation's Customer Service Department. The information, technical details and fixing instructions etc. included in this literature are given in good faith and apply to uses described. Kingspan Insulation does not accept responsibility for issues arising from using products in applications different from those described within this brochure or failure to correctly follow the information or instructions as described within this brochure.

Recommendations for use should be verified with a suitable expert or professional for suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan Insulation offers a technical advisory service (see above for contact details), the advice of which should be sought for uses of Kingspan Insulation products that are not specifically described herein. Please check that your copy of this literature is current by contacting the Kingspan Insulation Marketing Department.

® EcoTherm is a Registered Trademark of the Kingspan Group plc in the UK.  
All rights reserved. Registered in England & Wales, No. 01882722.

Registered Office: Pembridge, Leominster, Herefordshire HR6 9LA UK. VAT GB428602456