

D400 INTEGRITY



INTEGRITY 675 S



PYTHON 150

Features:

- Manufactured to BS EN 124 class D400
- BSI Kitemarked for third party assurance of quality
- Suitable for lower intensity traffic
- AMP™ anti-movement technology frames
- Non-rock three point suspension for stability and silent operation
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Options:

- Standard Locking
- High Security Locking
- Badging e.g. FW, SW, Motorway Comms
- Sealing Plates
- Safety Grids
- Security Plates

Standard Sizes		Standard Sizes			
Code	Legacy Code	Clear Opening (mm)	O/all Frame (mm)	Frame Depth (mm)	D/Tri Lids
INTEGRITY 450 S	KD800	450 x 450	585 x 585	100	1
INTEGRITY 6045 S	KD900	600 x 450	735 x 585	100	1
INTEGRITY 600 S	KD100	600 x 600	740 x 740	100	1
INTEGRITY 600 H	KD100-6	600 x 600	740 x 740	150	1
INTEGRITY 675 S	KD120	675 x 675	810 x 810	100	1
INTEGRITY 675 H	KD120-6	675 x 675	810 x 810	150	1

Standard Sizes				
Code	Clear Opening (mm)	O/all Frame (mm)	Frame Depth (mm)	D/Tri Lids
PYTHON 100*	600 x 600	750 x 750	100	1
PYTHON 150*	600 x 600	750 x 750	150	1
BRIO SC	600dia	850 x 850	100	-
WATT 100*	675 x 675	830 x 830	100	1
WATT 150*	675 x 675	840 x 840	150	1
SINCLAIR*	750 x 600	910 x 760	100	1
HUDSON 100*	1220 x 675	1365 x 830	100	2
HUDSON 150*	1220 x 675	1365 x 830	150	2

*Comply with CD534