

LIBERTY DRAIN™ 100
100 mm Wide
Innovative Channel Drainage


LIBERTY DRAIN™ 100


C 250 Grating


D 400 Grating


F 900 Grating


C250 Grate – Composite

Features:

- Manufactured to BS EN 1433 class C 250, D 400, F 900 as specified
- High quality polypropylene channel base
- Interlocking channel tongue & groove joints
- Smooth internal face for rapid flow rates
- Ductile Iron gratings
- 6 mm Safe-slot Ductile iron gratings – 8 point locking per metre
- 8 mm Safe-slot Composite gratings – Single bolt and bar locking per 500 mm grate
- Galvanised Steel edge rail

Options:

- Stepped Falls
- Integrated 90° turns
- Integrated 'T' junctions

Standard Sizes

Code	Grating	Int Width (mm)	Invert Depth (mm)	O/all Width (mm)	O/all Depth (mm)	Loading	Waterway (cm² per grate)	Weight (kg)
LDC100-6-50	Ductile	100	72	157	105	C 250	282	12
LDC100-6-100	Ductile	100	122	157	155	C 250	282	12
LDC100-6-150	Ductile	100	172	157	205	C 250	282	13
LDC100-8-50	Composite	100	72	157	105	C 250	144	4
LDC100-8-100	Composite	100	122	157	155	C 250	144	5
LDC100-8-150	Composite	100	172	157	205	C 250	144	6
LDD100-6-50	Ductile	100	72	159	106	D 400	235	14
LDD100-6-100	Ductile	100	122	159	156	D 400	235	15
LDD100-6-150	Ductile	100	172	159	206	D 400	235	16
LDF100-6-50	Ductile	100	72	159	106	F 900	217	18
LDF100-6-100	Ductile	100	122	159	156	F 900	217	19
LDF100-6-150	Ductile	100	172	159	206	F 900	217	20

Sump Unit

Standard Sizes

LDC100-6-400	Ductile	100	422	159	442	C 250	282	16
LDC100-8-400	Composite	100	422	159	442	C 250	144	12
LDD100-6-400	Ductile	100	422	159	442	D 400	235	17
LDF100-6-400	Ductile	100	422	159	442	F 900	217	19

LIBERTY DRAIN™ 100

100 mm Wide
Innovative Channel Drainage

