

One Hour Fire Rated Access Panels

Code: **GL150F** Standard



GL130F Standard

GL450F Standard

GL151F Lockable

GL131F Lockable

GL451F Lockable



Description:

Manthorpes' range of fire rated access panels provide various sizes of protected openings in ceilings and walls for access to building engineering services such as:

- Electrical Wiring Systems
- Fuse Boxes / Switches
- Controls / Connection Links
- Valves / Stopcocks / Plumbing

Each fire rated access panel includes a 'Square Lock & Key' to restrict unwanted access and is fire rated for up to 1 hour. The door is finished in powder coated white and can be over painted to blend with the surrounding surface.

The fire rated panel is a high quality, robust solution suitable for everyday use with all the discrete advantages required of an access panel.

The GL151F, GL131F and GL451F fire rated doors come complete with a cam lock and a set of keys for additional security.

Dimension Table:

Product Code:	A (mm)	B (mm)
GL150F / GL151F	200	150
GL130F / GL131F	300	300
GL450F / GL451F	450	450

Specification:

Packing Details	Individually Packaged in Cardboard Box
Materials	Zintec Mild Steel finished in Polyester Powder Coating (White)
Seal	PVC Foam
Insulation	Mineral Fibre (@30mm depth)
Weights	GL150F, GL151F - 1.2kg GL130F, GL131F - 2.2kg GL450F, GL451F - 4.1kg
Fire Assessment	WFRC No 516268

MANTHORPE BUILDING PRODUCTS LTD
MANTHORPE HOUSE
BRITAIN DRIVE
CODNOR GATE BUSINESS PARK
RIPLEY
DERBYSHIRE DE5 3ND

TEL: 01773 303 000
FAX: 01773 303 300
EMAIL:
mbp.care@manthorpebp.co.uk
WEB:
www.manthorpebp.co.uk

Drawn
MR 01.03.07

Issue Drawn
BH 08.07.25

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification without notice.

DRG No

MBP 8223

Issue

08