

SCALEMASTER INHIBITOR CONCENTRATE 250ml

| | |
|-----------------|--------------------|
| EAN | 5027639500423 |
| Product Code | 500423 |
| Volume | 250ml Bottle |
| Treats | 100 litre (10 rad) |
| Colour Code | Yellow |
| Leave in System | Yes |
| Liquid Colour | Brown |
| Box Quantity | 20 |

TECHNICAL HELPLINE 01785 811636



INHIBITOR - Prevents corrosion and hard water limescale precipitation, and is essential for protecting hot water heating systems and maintaining operational efficiency.

DOSE RATE: Bottle contains 250ml. Minimum dosage to achieve the NSF CIAS performance specification is 250ml per 100 litres of system water (up to 10 radiators). Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing of Scalemaster chemicals.

APPLICATION: Dose via the feed and expansion tank or via a radiator as per BS 7593:2019 **Leave in the system.** For best results first flush system with Scalemaster Cleanser or Scalemaster Sludge Remover.

HEALTH & SAFETY: Keep out of reach of children. Ensure there is sufficient ventilation of the area. If in contact with skin; wash immediately with plenty of soap and water. If in eyes; bathe the eye with running water for 15 minutes. If ingested; wash out mouth with water. If inhaled; consult a doctor if there are symptoms. Use protective gloves, clothing and eye protection. Ensure eye bath is to hand. Safety Data Sheet available on request. Do not use with PRIMATIC single-feed cylinders.

STORAGE & DISPOSAL: Store in a cool, well-ventilated area. Keep container tightly closed. Do not allow to freeze. Dispose of contents and container in accordance with regional or national regulations.

Product has no maximum shelf life when stored under normal conditions (4-40°C), however it is recommended that end users use the product within 6 months of purchase.