



UK Declaration of Performance

Kingspan GreenGuard® GG300

1001.UKDoP.GG300.004

Kingspan GreenGuard $^{\circledR}$ GG300 Thermal insulation for buildings Unique identification code of the product-type:

Intended use/es:

Manufacturer: Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK System 4 (Reaction to fire), System 3 (Other Properties) BS EN 13164:2012+A1:2015 System/s of AVCP:

Harmonised technical specification:

University of Salford:1145. BBA:0836 **UK Assessment Body:**

Essential characteristics		Performance
Thermal resistance	Thermal resistance R _D ((m².K)/W)	d _N 30mm 0.90 d _N 40mm 1.20 d _N 50mm 1.50 d _N 60mm 1.80 d _N 70mm 2.10 d _N 80mm 2.40 d _N 100mm 3.00 d _N 120mm 3.60 d _N 140mm 4.20 d _N 150mm 4.50 d _N 180mm 5.45
	Thermal conductivity λ_D (W/(m.K)) Thickness tolerance	$\begin{array}{cccc} d_N \ 30\text{-}180 & 0.033 \\ \\ d_N \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability characteristics	NPD
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensional stability under specified temperature and humidity conditions	DS(70,90)
	Deformation under specified compressive load and temperature conditions	NPD
Compressive strength	Compressive stress or compressive strength	(10/Y) 300
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR100
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Long term water absorption by total immersion	NPD
	Long term water absorption by diffusion	NPD
	Freeze-thaw resistance after long term water absorption by diffusion	NPD
Water vapour permeability	Water vapour transmission	NPD
Closed cell content	Closed cell content	NPD
Continuous Glowing combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		





UK Declaration of Performance

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....

lidely

Siobhan O'Dwyer Managing Director Selby, England, UK Date signed: 24/03/2025 Issue Number: 004



For the most up-to-date version of the Declaration of Performance please scan or <u>click here</u>. To access pre-existing product information or information relating to previously sold/discontinued products please email <u>literature@kingspaninsulation.co.uk</u>