



UK Declaration of Performance

Kingspan Thermaroom® TR24

1000.UKDoP.TR24.004

1001.UKDoP.TR24.004

Unique identification code of the product-type:

Kingspan Thermaroom® TR24

Intended use/es:

Thermal insulation for buildings

Manufacturer:

Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK

System/s of AVCP:

System 4 (Reaction to fire), System 3 (Other Properties)

Designated technical specification:

BS-EN 13165:2012+A2:2016

UK Assessment/Notified body/ies:

University of Salford: 1145, BBA: 0836

Essential characteristics		Performance	
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	d _N 30mm d _N 40mm d _N 50mm d _N 60mm d _N 70mm d _N 80mm d _N 90mm d _N 100mm d _N 120mm d _N 130mm d _N 140mm d _N 150mm	1.10 1.45 1.85 2.20 2.55 3.20 3.60 4.00 5.00 5.40 5.80 6.25
	Thermal conductivity λ_D (W/(m.K))	Flat board - Pembroke Plant 1000 d _N < 80mm d _N 80-119mm d _N ≥ 120mm Flat board – Selby Plant 1001 d _N < 80mm d _N 80-119mm d _N ≥ 120mm	 0.027 0.025 0.024 0.027 Not manufactured 0.024
	Thickness tolerance	T2	
Reaction to fire	Reaction to fire	F	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD	
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD	
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance R_D ((m ² .K)/W)	Thermal resistance as table above	
	Thermal conductivity λ_D (W/(m.K))	Flat board - Pembroke Plant 1000	

UK Declaration of Performance

		dN < 80mm 0.027 dN 80-119mm 0.025 dN ≥ 120mm 0.024 Flat board – Selby Plant 1001 dN < 80mm 0.027 dN 80-119mm Not manufactured dN ≥ 120mm 0.024
	Durability characteristics	NPD
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1
	Deformation under specified compressive load and temperature conditions	NPD
	Determination of the aged values of thermal resistance and thermal conductivity	λD 0,024, 0.025, 0,027 W/m-K
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing combustion	Glowing combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)



UK Declaration of Performance

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Siobhan O'Dwyer'.

.....
Siobhan O'Dwyer
Managing Director
Pembroke, Selby, England, UK
Date signed: 30/06/2025
Issue Number: 004



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk