

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EVERBUILD Lead Mate Sealant

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

|                          |                    |                                                                       |
|--------------------------|--------------------|-----------------------------------------------------------------------|
| Precautionary statements | P101               | If medical advice is needed, have product container or label at hand. |
|                          | P102               | Keep out of reach of children.                                        |
|                          | <b>Prevention:</b> |                                                                       |
|                          | P261               | Avoid breathing mist or vapours.                                      |
|                          | P264               | Wash skin thoroughly after handling.                                  |
|                          | P280               | Wear protective gloves/ eye protection/ face protection.              |
|                          | <b>Disposal:</b>   |                                                                       |
|                          | P501               | Dispose of contents/container in accordance with local regulation.    |

### Hazardous components which must be listed on the label:

trimethoxyvinylsilane

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

| Chemical name                                                                                                | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                          | Concentration<br>(% w/w) |
|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| bis(ethyl acetoacetato-O1',O3)bis(2-methylpropan-1-olato)titanium<br>Contains:<br>2-methylpropan-1-ol <= 2 % | 83877-91-2<br>281-161-6<br>01-2119968551-31-XXXX      | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT SE 3; H336<br>(Central nervous system) | >= 2,5 - < 3             |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

|                                                                          |                                                                 |                                                                                                                                                                                                                                                |                |
|--------------------------------------------------------------------------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| trimethoxyvinylsilane<br>Contains:<br>tetramethyl orthosilicate <= 0,2 % | 2768-02-7<br>220-449-8<br>014-049-00-0<br>01-2119513215-52-XXXX | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Skin Sens. 1B; H317<br><br>Acute toxicity estimate<br><br>Acute inhalation toxicity (vapour): 16,8 mg/l                                                                                            | >= 1 - < 2,5   |
| methanol                                                                 | 67-56-1<br>200-659-6<br>603-001-00-X<br>01-2119433307-44-XXXX   | Flam. Liq. 2; H225<br>Acute Tox. 3; H301<br>Acute Tox. 3; H331<br>Acute Tox. 3; H311<br>STOT SE 1; H370<br><br>specific concentration limit<br>STOT SE 1; H370<br>>= 10 %<br><br>specific concentration limit<br>STOT SE 2; H371<br>3 - < 10 % | >= 0,1 - < 0,5 |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions  
Excessive lachrymation  
See Section 11 for more detailed information on health effects and symptoms.

Risks : irritant effects  
sensitising effects  
  
May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

use.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components | CAS-No.                                                                                                                                                                      | Value type (Form of exposure) | Control parameters * | Basis *    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| methanol   | 67-56-1                                                                                                                                                                      | TWA                           | 200 ppm<br>260 mg/m3 | 2006/15/EC |
|            | Further information: Indicative, Identifies the possibility of significant uptake through the skin                                                                           |                               |                      |            |
|            |                                                                                                                                                                              | TWA                           | 200 ppm<br>266 mg/m3 | GB EH40    |
|            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                      |            |
|            |                                                                                                                                                                              | STEL                          | 250 ppm<br>333 mg/m3 | GB EH40    |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

##### Occupational exposure limits of decomposition products

| Components | CAS-No.                                                                                                                                                                      | Value type (Form of exposure) | Control parameters * | Basis *    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| methanol   | 67-56-1                                                                                                                                                                      | TWA                           | 200 ppm<br>260 mg/m3 | 2006/15/EC |
|            | Further information: Indicative, Identifies the possibility of significant uptake through the skin                                                                           |                               |                      |            |
|            |                                                                                                                                                                              | TWA                           | 200 ppm<br>266 mg/m3 | GB EH40    |
|            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                      |            |
|            |                                                                                                                                                                              | STEL                          | 250 ppm<br>333 mg/m3 | GB EH40    |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use            | Exposure routes | Potential health effects | Value     |
|----------------|--------------------|-----------------|--------------------------|-----------|
| methanol       | Workers            | Skin contact    |                          | 40 mg/m3  |
|                | Exposure time: 8 h |                 |                          |           |
|                | Consumers          | Skin contact    |                          | 260 mg/m3 |
|                | Exposure time: 8 h |                 |                          |           |

#### 8.2 Exposure controls

##### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : paste  
Colour : various  
Odour : slight

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 61 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : 160.000 - 330.000 mPa.s (15 - 20 °C)

Viscosity, kinematic : > > 30 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,01 hPa

Density : 1,35 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products : methanol

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute toxicity estimate: 16,8 mg/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : LD50: 3.540 mg/kg

### **Skin corrosion/irritation**

Not classified due to lack of data.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

Not classified due to lack of data.

#### **STOT - repeated exposure**

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

##### Product:

Additional ecological information : There is no data available for this product.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

#### 14.2 UN proper shipping name

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

#### 14.3 Transport hazard class(es)

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

#### 14.4 Packing group

|                  |   |                                   |
|------------------|---|-----------------------------------|
| ADR              | : | Not regulated as a dangerous good |
| IMDG             | : | Not regulated as a dangerous good |
| IATA (Cargo)     | : | Not regulated as a dangerous good |
| IATA (Passenger) | : | Not regulated as a dangerous good |

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 0,2% w/w  
no VOC duties

Directive 1999/13/EC  
Volatile organic compounds (VOC) content: 32,5 g/l  
VOC content valid only for coating materials used on wood surfaces  
Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,2% w/w

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

|      |                                        |
|------|----------------------------------------|
| H225 | : Highly flammable liquid and vapour.  |
| H226 | : Flammable liquid and vapour.         |
| H301 | : Toxic if swallowed.                  |
| H311 | : Toxic in contact with skin.          |
| H315 | : Causes skin irritation.              |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage.           |
| H331 | : Toxic if inhaled.                    |
| H332 | : Harmful if inhaled.                  |
| H335 | : May cause respiratory irritation.    |
| H336 | : May cause drowsiness or dizziness.   |
| H370 | : Causes damage to organs.             |

### Full text of other abbreviations

|                  |                                                         |
|------------------|---------------------------------------------------------|
| Acute Tox.       | : Acute toxicity                                        |
| Eye Dam.         | : Serious eye damage                                    |
| Flam. Liq.       | : Flammable liquids                                     |
| Skin Irrit.      | : Skin irritation                                       |
| Skin Sens.       | : Skin sensitisation                                    |
| STOT SE          | : Specific target organ toxicity - single exposure      |
| 2006/15/EC       | : Europe. Indicative occupational exposure limit values |
| GB EH40          | : UK. EH40 WEL - Workplace Exposure Limits              |
| 2006/15/EC / TWA | : Limit Value - eight hours                             |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## EVERBUILD Lead Mate Sealant

Date of last issue: 13.02.2025  
Revision Date: 03.07.2025

Version 13.2

Print Date 03.07.2025

|                |   |                                                                                                                                                                                                                                      |
|----------------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GB EH40 / TWA  | : | Long-term exposure limit (8-hour TWA reference period)                                                                                                                                                                               |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period)                                                                                                                                                                               |
| ADR            | : | European Agreement concerning the International Carriage of Dangerous Goods by Road                                                                                                                                                  |
| CAS            | : | Chemical Abstracts Service                                                                                                                                                                                                           |
| DNEL           | : | Derived no-effect level                                                                                                                                                                                                              |
| EC50           | : | Half maximal effective concentration                                                                                                                                                                                                 |
| GHS            | : | Globally Harmonized System                                                                                                                                                                                                           |
| IATA           | : | International Air Transport Association                                                                                                                                                                                              |
| IMDG           | : | International Maritime Code for Dangerous Goods                                                                                                                                                                                      |
| LD50           | : | Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)                                                                                               |
| LC50           | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL         | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL            | : | Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT            | : | Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC           | : | Predicted no effect concentration                                                                                                                                                                                                    |
| REACH          | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC           | : | Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB           | : | Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

#### Classification of the mixture:

|              |      |
|--------------|------|
| Eye Irrit. 2 | H319 |
| Skin Sens. 1 | H317 |

#### Classification procedure:

|                    |
|--------------------|
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN