

Novia® Tape and Sealant Guidance

Novia Ltd supplies a wide range of tapes and sealants which should be used in conjunction with Novia construction membranes. It is essential that Novia tapes are used in conjunction with Novia membranes. Please refer to product datasheets for installation guidance.

Product Group	Novia Tape		Sizes Available	Approx no. required per roll of membrane
Breather Membranes	Tape 1	Novia Double Sided Lap Tape (DSLT) Double sided reinforced lap tape.	50mm x 25m	3-4 rolls
	Tape 2	Novia Single Sided Breather Membrane Lap Tape (BMLT) Single sided lap tape.	50mm x 25m	3-4 rolls
			75mm x 25m	
		Novia Single Sided Ultraviolet Lap Tape (UFLT) Single sided lap tape, with improved UV resistance.	75mm x 25m	3-4 rolls
Air & Vapour Control Layers	Tape 1	Novia Double Sided Butyl Tape Black butyl joint and sealing tape.	100mm x 10m x 1.5mm	6-10 rolls
			50mm x 10m x 1.5mm	
			30mm x 30m x 1.5mm	3-5 rolls
			15mm x 22.5m x 2mm	
	Tape 2	Novia Metallised BOPP Tape (Standard & Cold Weather options) High performance metallised lap tape with high strength tear resistance.	60mm x 50m	1-2 rolls
			48mm x 45m	
			72mm x 45m	
	Sealant	Novia AirSeal310 Sealant Cartridge A blue sealant cartridge with excellent cold weather adhesion.	310ml	1 cartridge provides enough for 1m running length at a 20mm x 15mm bead
		Novia AirSeal310 FR Sealant Cartridge – Fire Rated. A blue emulsion-based sealant fire tested to BS 1366-4. Recommended to be used when installing Novia VC4000 FR.	310ml	
Radon Gas Barrier*	Tape 1	Novia Double Sided Butyl Tape Black butyl joint and sealing lap tape. Minimum 50mm width recommended.	100mm x 10m	6-10 rolls
			50mm x 10m	
	Tape 2	Novia Aluminium Foil Lap Tape High performance metallised lap tape. Minimum 96mm width recommended.	96mm x 45m	1-2 rolls
Methane Pro 390 Gas Barrier*	Tape 1	Novia Double Sided Butyl Tape Black butyl joint and sealing lap tape. Minimum 50mm width required	100mm x 10m	6-10 rolls
			50mm x 10m	
	Tape 2	Novia Aluminium Foil Lap Tape High performance metallised lap tape. Minimum 96mm width required.	96mm x 45m	1-2 rolls

*Can be welded

Due to the varied nature of different installations, all quantities suggested are guidance only.