


**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2015




Version number 14

Revision: 18.08.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** Surface Primer FG 35
- **Article number:** FG 35
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
CARLISLE® Construction Materials GmbH  
Schellerdamm 16  
D-21079 Hamburg, Germany  
Telefon/Phone: +49 (0)40 788933-200
-  **CARLISLE Construction Materials Ltd**  
Lancaster House, Fountain Court  
Concorde Way  
Millenium Business Park  
GB - Mansfield Nottinghamshire NG19 7DW
- **Further information obtainable from:**  
Phoenix CT, Abteilung Umweltschutz  
Hannoversche Str. 88 D - 21079 Hamburg  
Tel.: ++49 (0)40 7667-2794  
E-Mail: [sdb@comp.contitech.de](mailto:sdb@comp.contitech.de)
- **1.4 Emergency telephone number:** +49 (0)40 7667 2233

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
-  **GHS02 flame**  
Flam. Liq. 2      H225 Highly flammable liquid and vapour.
-  **GHS09 environment**  
Aquatic Acute 1      H400 Very toxic to aquatic life.  
Aquatic Chronic 1      H410 Very toxic to aquatic life with long lasting effects.
-  **GHS07**  
Skin Irrit. 2      H315 Causes skin irritation.  
STOT SE 3      H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
cyclohexane

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 1)

· **Hazard statements**

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P321 Specific treatment (see on this label).
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

- Contains zinc bis(dibutyldithiocarbamate). May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 110-82-7 EINECS: 203-806-2	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 136-23-2 EINECS: 205-232-8	zinc bis(dibutyldithiocarbamate) ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≤ 0.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

GB

(Contd. on page 3)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 2)

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).  
Do not use sawdust or other combustible materials.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
When working with the product N-Nitrosamines can be liberated. N-Nitrosamines are carcinogenic Group 2.  
Limit (D): general background value 0,1 µg/m<sup>3</sup>

(Contd. on page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 3)

## 110-82-7 cyclohexane

WEL Short-term value: 1050 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 350 mg/m<sup>3</sup>, 100 ppm

## 141-78-6 ethyl acetate

WEL Short-term value: 400 ppm  
Long-term value: 200 ppm

· **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

#### · Respiratory protection:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form: Fluid  
Colour: Black

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 4)

· <b>Odour:</b>	Solvent-like
· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	60 °C
· <b>Flash point:</b>	-20 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	250 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.8 Vol %
<b>Upper:</b>	8.3 Vol %
· <b>Vapour pressure at 20 °C:</b>	104 hPa
· <b>Density at 20 °C:</b>	0.84 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 40 °C:</b>	900 mm <sup>2</sup> /s
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	65.1 %
<b>Solids content:</b>	35.0 %
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 5)

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

**110-82-7 cyclohexane**

Oral	LD50	12705 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
-----------	--

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14




Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b>	UN1133
· <b>ADR, IMDG, IATA</b>	
· <b>14.2 UN proper shipping name</b>	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS, special provision 640D
· <b>ADR</b>	ADHESIVES, MARINE POLLUTANT
· <b>IMDG</b>	ADHESIVES
· <b>IATA</b>	
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids.
· <b>Label</b>	3
· <b>IMDG</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>14.4 Packing group</b>	II
· <b>ADR, IMDG, IATA</b>	
· <b>14.5 Environmental hazards:</b>	Product contains environmentally hazardous substances: cyclohexane
· <b>Marine pollutant:</b>	Yes
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E,S-D
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 7)

**· Transport/Additional information:**

**· ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

**· IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN1133, ADHESIVES, special provision 640D,  
ENVIRONMENTALLY HAZARDOUS, 3, II

## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	65.1

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Other regulations, limitations and prohibitive regulations** Subject to the regulations for N-Nitrosamines.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This version replaces the version of: (see header line)

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 18.08.2015

Version number 14

Revision: 18.08.2015

**Trade name: Surface Primer FG 35**

(Contd. of page 8)

*H410 Very toxic to aquatic life with long lasting effects.*

*H411 Toxic to aquatic life with long lasting effects.*

· **Department issuing MSDS:** PCT GmbH Abteilung Umweltschutz

· **Contact:** Hr. Dr. Laugwitz

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 2: Flammable liquids, Hazard Category 2*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*

*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*

*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*

GB