

SCALEMASTER DE-SCALER CONCENTRATE 250ml

EAN	5027639500430
Product Code	500430
Volume	250ml Bottle
Treats	100 litre (10 rad)
Colour Code	Red
Leave in System	Yes
Liquid Colour	Colourless
Box Quantity	20

TECHNICAL HELPLINE 01785 811636



DE-SCALER - FOR ESTABLISHED CENTRAL HEATING SYSTEMS. Restores and maintains heat exchanger efficiency in hard water areas and stops boiler noise by re-dissolving limescale precipitation on heat exchanger surfaces.

DOSE RATE: Bottle contains 250ml, this treats up to a 100 litre (10 radiator) system at 0.25% solution. Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Scalemaster products.

APPLICATION: To prevent 'kettling' and boiler noise, (first check noise is not caused by system design or mechanical fault before application). Dose via the feed and expansion tank or via a radiator as per BS 7593:2019 **Leave in system**. For best results use with Scalemaster Inhibitor.

HEALTH & SAFETY: Keep out of reach of children. Ensure there is sufficient ventilation of the area. If in contact with skin; wash immediately with plenty of soap and water. If in eyes; bathe the eye with running water for 15 minutes. If ingested; wash out mouth with water. If inhaled; consult a doctor if there are symptoms. Use protective gloves, clothing and eye protection. Ensure eye bath is to hand. Safety Data Sheet available on request. Do not use with PRIMATIC single-feed cylinders.¹

STORAGE & DISPOSAL: Store in a cool, well-ventilated area. Keep container tightly closed. Do not allow to freeze. Dispose of contents and container in accordance with regional or national regulations.

Product has no maximum shelf life when stored under normal conditions (4-40°C), however it is recommended that end users use the product within 6 months of purchase.