

SLUDGE REMOVER CONCENTRATE 250ml

EAN	5027639500454
Product Code	50054
Volume	250ml Bottle
Treats	100 litre (10 rad)
Colour Code	Pale Blue
Leave in System (Min)	2 Hours
Leave in System (Max)	2 Weeks
Liquid Colour	Clear
Box Quantity	20
Shelf Life	Minimum 3 Years

TECHNICAL HELPLINE 01785 811636



Sludge Remover - FOR THE REGENERATION OF ESTABLISHED HEATING SYSTEMS. Removes (black) iron oxide corrosion products by flushing and restores circulation and system performance. Should be left in system minimum 2 hours, maximum 2 weeks.

Dose Rate:

Bottle contains 250ml. This treats up to a 100 litre (10 radiator) system. Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Scalemaster products.

Application:

Dose via the feed and expansion tank or via a radiator as per BS/7593:2006. Run system on normal heating cycle. Leave in system minimum 2 hours, maximum 2 weeks. **Flush out** until water is clear to remove all contaminants.

Protection:

At final fill add Scalemaster Corrosion Inhibitor to prevent scale and corrosion.

Health & Safety:

Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. Do not use with PRIMATIC single feed cylinders.