

SL-S SINGLE TANK NON-ELECTRIC WATER SOFTENER

EAN	5027639900292
Product Code	9002292
People	Up to 4
Height	492mm
Depth	475mm
Depth (With Connectors)	532mm
Width	235mm
Approximate Regeneration Time	15 Minutes
Resin Volume	4.5 Litre
Salt used per regeneration	0.27kg
Water used per regeneration	25 Litres
Flow Rate @ 1 bar Pressure Drop	30 L/Minute
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Installation Orientation	Rear Only
Minimum/Maximum Operating Temp	2° - 40°C
Minimum/Maximum Working Pressure	1.5 bar min / 6 bar max*
* Pressure Reducing Valve Must Be Fitted Over 6 bar	
Maximum Soft Water (at 200ppm)	689 Litres
Maximum Soft Water (at 300ppm)	400 Litres
What salt to use	Tablet or Block
Warranty	2 Years Parts and Labour*



Requires one of the following installation kits

900803	15mm Standard Installation Kit
900858	22mm Hi-Flow Hoses x 2
900827	Combi installation Kit
900810	22mmHi-Flow Installation Kit

*** IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

TECHNICAL HELPLINE 01785 811636

Hardness Level	100	125	150	200	250	350	525
Litres Between Regeneration	1358	1083	905	689	531	400	256