

SL-X SINGLE TANK NON-ELECTRIC WATER SOFTENER

EAN	5027639900308
Product code	900308
People	Up to 6
Height	601mm
Depth	632mm
Depth (With Connectors)	685mm
Width	345mm
Approximate Regeneration Time	18 Minutes
Resin Volume	15.5 Litres
Salt used per regeneration	0.59kg
Water used per regeneration	38 Litres
Flow Rate @ 1 bar Pressure Drop	45 L/Minute
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Installation Orientation	Rear Only
Minimum/Maximum Operating Temp	2° - 40°C
Minimum/Maximum Working Pressure	1.5 bar Max / 6 bar Minimum*
* Pressure Reducing Valve Must Be Used Over 6 bar	
Maximum Soft Water (at 200ppm)	1325 Litres
Maximum Soft Water (at 300ppm)	757 Litres
What salt to use	Tablet or Block
Warranty	2 Years Parts and Labour*



Requires one of the following installation kits

900803	15mm Standard Installation Kit
900858	22mm Hi-Flow Hoses x 2
900827	Combi installation Kit
900810	22mmHi-Flow Installation Kit

*** IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

TECHNICAL HELPLINE 01785 811636

Hardness Level	125	150	200	250	300	500	850
Litres Between Regeneration	2158	1779	1325	1060	757	530	303