



Soudal Aluminium Foil Tape

Date: 07/02/2024 – NEW Page 1 from 1

Technical data

Material	Backing: Aluminium Foil
	Liner: Glassine paper
Total thickness	0.07mm
Tensile strength	6.4 N/cm
Adhesion	3.2 N/cm
Service temperature	-30°C to 100°C
Elongation	5%

Product description

Soudal Aluminium Foil Tape is an all purpose foil tape with thermal and vapour resistance properties.

Properties

- Excellent temperature resistance properties.
- Excellent vapour resistance properties.
- UV Resistant.

Applications

- Sealing of aluminium foil faced insulation boards.
- For securing duct seams, connections and ioints.
- Protection of exteriors against the weather.

Packaging:

Colours: foil

Packaging: tape roll 45mtr length. Available widths are 48mm, 72mm, 100mm.

Shelf life

In unopened packaging in a dry and cool storage at temperatures between +15°C and +25°C: 12 months.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com