

15mm SCALEMASTER MAGNETIC GOLD

| | |
|-------------------|--------------------|
| EAN | 5027639400143 |
| Product Code | 400143 |
| Pipe Diameter | 15mm |
| Body Material | Copper |
| Fitting Type | Compression |
| Maximum Flow Rate | 32 litres / minute |
| Length | 170mm |
| Diameter | 35mm |
| Weight | .51kg |
| Guarantee | 3 Years |

TECHNICAL HELPLINE 01785 811636



SINGLE
APPLIANCE
PROTECTION



Features & Benefits

- Slip Couplings for easy fit
- Earth bonding not required
- Needs no chemicals or power
- Easily installed
- No moving parts, no maintenance required
- 3 Year product performance guarantee
- Manufactured in the UK
- Scalemaster patented technology
- WRAS Approved Product
- Single appliance protection
- Saves on energy costs

Installation Instructions

Magnetic Scale Inhibitors are only suitable for individual Appliance Protection.

- Plumb into the cold water supply pipe a minimum of one metre to a maximum of 2 metres before the appliance
- Operating temperature 4°C - 40°C
- Do not allow to freeze
- Maximum operating pressure 8 bar
- Do not solder
- Compression fitting torque setting 30 - 35 Nm
- Installation should be made to comply with all local byelaws and building regulations

Additional Information: Using a kettle - Magnetic effect changes hard water scale into tiny particles. The particles pass out of hot water heating systems in the flow of water called off for use. However to prevent an accumulation of scale particles in a kettle pour away any unused hot water and refill with cold.

22mm SCALEMASTER MAGNETIC GOLD

| | |
|-------------------|--------------------|
| EAN | 5027639400259 |
| Product Code | 400259 |
| Pipe Diameter | 22mm |
| Body Material | Copper |
| Fitting Type | Compression |
| Maximum Flow Rate | 36 litres / minute |
| Length | 165mm |
| Diameter | 35mm |
| Weight | .51kg |
| Guarantee | 3 Years |



SINGLE
APPLIANCE
PROTECTION



Features & Benefits

- Slip Couplings for easy fit
- Earth bonding not required
- Needs no chemicals or power
- Easily installed
- No moving parts, no maintenance required
- 3 Year product performance guarantee
- Manufactured in the UK
- Scalemaster patented technology
- WRAS Approved Product
- Single appliance protection
- Saves on energy costs

Installation Instructions

Magnetic Scale Inhibitors are only suitable for individual Appliance Protection.

- Plumb into the cold water supply pipe a minimum of one metre to a maximum of 2 metres before the appliance
- Operating temperature - Cold water use only
- Do not allow to freeze
- Maximum operating pressure 8 bar
- Do not solder
- Compression fitting torque setting 50 Nm

Installation should be made to comply with all local byelaws and building regulations

Additional Information: Using a kettle - Magnetic effect changes hard water scale into tiny particles. The particles pass out of hot water heating systems in the flow of water called off for use. However to prevent an accumulation of scale particles in a kettle pour away any unused hot water and refill with cold.