Wallbarn - Technical Datasheet

5mm Fixed Height Pedestal



SP-RUB-005-Z

Product Description

Fixed circular PVC pads designed to provide a minimum amount of height from the surface when installing timber decking and paving systems. A separate loose cross spacer can be placed on the top surface to provide the symmetrical and tight fitting for the paving system. For both timber decking and paving, the circular pads allow the roof to be ventilated and at the same time provides easy access for inspection.

Application

The PVC pads can be laid on all secure and stable floor surfaces allowing inspection under slabs or decking without demolition. Installation in external areas helps to protect the waterproof surface and allows for the practical use of a terrace.

Design

The PVC pad is circular measuring 150mm in diameter with a smooth, flat base and upper surface. It is 5mm in height. The cross spacer is made from polypropylene and is available in a variety of thicknesses. The cross spacer is not fixed to the PVC pad.

Wallbarn - Technical Datasheet

Technical Data

The PVC pads can withstand a temperature range from -40 °C to +75 °C. This pad material is particularly resistant to sudden temperature changes; it resists acids, alkalines and atmospheric agents.

Material	**PVC**
Thickness	**5mm**
Outer Diameter	**150mm**
Weight Tolerance/ Bearing Capacity	**8,000Kg**
Appearance	**Flat Disc both sides**
Optional Accessory	
Width of Cross Spacers available	**3mm, 4mm & 5mm**
Cross Spacer Height	**10mm**





Wallbarn Ltd
Unit 16 Capital Business Centre
22 Carlton Road, South Croydon. CR2 0BS

Phone : 0208 916 2222 Email : sales@wallbarn.com Website : www.wallbarn.com