Wallbarn - Technical Datasheet

7mm Fixed Height Pedestal



SP-RUB-007-PAVING-Z



SP-RUB-007-DECKING-Z

Product Description

Ultra-thin PVC pads 7mm in height for paving and timber decking that provide adequate drainage by lifting the slabs and joist frame from the deck. For paving there is a lugged headpiece that sits into a slight indent which is moulded into the PVC pad so that the overall height of the pad remains 7mm. Similarly, for timber decking there is a lugged headpiece into which the joist frame will sit. There is also an alternative TD plus headpiece where installers can screw the timber joist in place through the side bars for secure fitting.

Application

The PVC pads can be laid on all secure and stable floor surfaces allowing inspection under slabs or decking without demolition. Installation in external areas helps to protect the waterproof surface and allows for the practical use of a terrace.

Design

The PVC pad is circular measuring 150mm in diameter. The upper surface is moulded into a series of circular ridges and grooves which encourage rainwater to run off the surface of the pad. No mechanical fixing is required as the weight and stability of the paving and timber decking joist frame will hold everything securely in place.

Wallbarn - Technical Datasheet

Technical Data

The PVC pads can withstand a temperature range from -40 °C to +75 °C. This pad material is particularly resistant to sudden temperature changes; it resists acids, alkalines and atmospheric agents.

Material	**PVC**
Thickness	**7mm**
Outer Diameter	**150mm**
Weight Tolerance/ Bearing Capacity	**8,000Kg**
Paving Headpiece (Lug Width)	**2.2mm standard width (4, 6, 8 & 10mm available)**
Decking Headpiece (distance between lugs)	**60mm**
Lug Height	**15mm**
Drainage Channels	**6**





Wallbarn Ltd
Unit 16 Capital Business Centre
22 Carlton Road, South Croydon. CR2 0BS

Phone : 0208 916 2222 Email : sales@wallbarn.com Website : www.wallbarn.com