

LEAD FLASHING

WEIGHT CHART

WIDTH		CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8		WIDTH	
mm	Nom Imp	GREEN		BLUE		RED		BLACK		WHITE		ORANGE		mm	Nom Imp
		3 metre Kg	6 metre Kg	3 metre Kg	6 metre Kg	3 metre Kg	6 metre Kg	3 metre Kg	6 metre Kg	3 metre Kg	6 metre Kg	3 metre Kg	6 metre Kg		
150	6"	7.0	13.5	9.0	18.5	11.5	23.0	13.5	27.0	16.0	32.0	18.0	36.0	150	6"
180	7"	8.0	16.0	11.0	22.0	14.0	27.5	16.5	32.5	19.5	38.5	22.0	43.5	180	7"
210	8"	9.5	19.0	13.0	26.0	16.0	32.0	19.0	38.0	22.5	45.0	25.5	51.0	210	8"
240	9"	11.0	21.5	15.0	29.5	18.5	36.5	22.0	43.5	26.0	51.5	29.0	58.0	240	9"
270	10"	12.0	24.5	16.5	33.0	20.5	41.0	24.5	49.0	29.0	58.0	32.5	65.0	270	10"
300	12"	13.5	27.0	18.5	36.5	23.0	45.5	27.0	54.0	32.0	64.5	36.0	72.5	300	12"
330	13"	15.0	30.0	20.0	40.5	25.0	50.5	30.0	59.5	35.5	71.0	40.0	80.0	330	13"
360	14"	16.0	32.5	22.0	44.0	27.5	55.0	32.5	65.0	38.5	77.0	43.5	87.0	360	14"
390	15"	17.5	35.0	24.0	48.0	30.0	59.5	35.0	70.5	42.0	83.5	47.0	94.0	390	15"
420	16"	19.0	38.0	26.0	51.5	32.0	64.0	38.0	76.0	45.0	90.0	51.0	101.5	420	16"
450	18"	20.5	40.5	27.5	55.0	34.5	68.5	40.5	81.5	48.0	96.5	54.5	109.0	450	18"
480	19"	21.5	43.0	29.5	59.0	36.5	73.0	43.5	87.0	51.5	103.0	58.0	116.0	480	19"
510	20"	23.0	46.0	31.0	62.5	39.0	78.0	46.0	92.0	55.0	109.5	61.5	123.0	510	20"
540	21"	24.5	48.5	33.0	66.0	41.0	82.5	49.0	97.5	58.0	116.0	65.0	130.5	540	21"
570	22"	26.0	51.5	35.0	70.0	43.5	87.0	51.5	103.0	61.0	122.0	69.0	138.0	570	22"
600	24"	27.0	54.0	37.0	73.5	46.0	91.5	54.0	108.5	64.5	128.5	72.5	145.0	600	24"
750	30"	34.0	67.5	46.0	92.0	57.0	114.5	68.0	135.5	80.5	161.0	90.5	181.0	750	30"
900	36"	40.5	81.0	55.0	110.0	68.5	137.0	81.5	162.5	96.5	193.0	109.0	217.5	900	36"
1000	39"	45.0	90.0	61.0	122.5	76.0	152.5	90.5	-	107.0	-	121.0	-	1000	39"
1050	41"	47.5	94.5	64.5	128.5	80.0	160.0	95.0	-	112.5	-	127.0	-	1050	41"
1200	47"	54.0	108.0	73.5	147.0	91.5	183.0	108.5	-	128.5	-	145.0	-	1200	47"
1350	53"	61.0	121.5	83.0	165.5	103.0	206.0	122.0	-	145.0	-	163.0	-	1350	53"
1400	55"	63.0	126.0	86.0	171.5	107.0	213.5	126.5	-	150.0	-	169.0	-	1400	55"
WEIGHT per sq.m		15.0kg		20.4kg		25.4kg		30.1kg		35.7kg		40.3kg		WEIGHT per sq.m	
THICKNESS		1.32mm (0.052")		1.80mm (0.071")		2.24mm (0.088")		2.65mm (0.104")		3.15mm (0.124")		3.55mm (0.140")		THICKNESS	

Flashings: Standard flashings are shown in the above chart, however, any widths from 100mm (4") to 1400mm (4'7") can be produced.

Lead flashings theory weights:

All theory weights are subject to ±5% tolerance.

The theory weight of lead sheet in kgs can be calculated using the following formula:

No. of pieces x Length in metres x Width in metres x Thickness in mm x 11.34

Useful conversion factors:

1mm = 0.039 Inches

1m = 3.281 Feet

1m = 39,370 Inches

1 Inch = 25.4mm

1 Foot = 304.8mm

1 Yard = 914.4mm

**DON'T FORGET TO APPLY
PATINATION OIL**