



WorkPro Slot

Underlay

Closed cell
polyolefin
foam
underlay
designed for
**maximum
bonding**

■ Bond...max bond

The unique pre-cut perpendicular slots let you put beads of high strength elastic adhesive directly onto the subfloor, for the perfect bond with the floor covering.

■ Keep in shape

WorkPro Slot recovers quickly from compression – in other words, it always makes sure your floor's fully supported under even the heaviest load.

■ That warm feeling

By allowing a bond between the floor and subfloor, WorkPro Slot is ideal for laying over underfloor heating systems built into the subfloor.

Technical Data

Properties	Unit	Value	Method
Impact Sound Reduction	dB	≥ 22	ISO 140-8
Thermal Resistance measured at 10°C	m ² k/W	0.088	ISO 8301
Performance —	k Pa	3	EN 1606
Compressive Creep	kg/m ³	300	EN 1363
The maximum load which can be applied to the underlay so that the loss in thickness remains below 10% after 10 years loading time.			
Joint Protection —	k Pa	28	ISO 844
Compressive Strength and measured at 0.5mm Deformation	kg/m ³	2800	EN 13163

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Block H, Pickerings Road,
Widnes, Cheshire WA8 8XW
Tel: 0151 495 3434
Fax: 0151 420 9062

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

Simply Better

Heavy
Traffic

Wood



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use*

*Suitable for hotels and public buildings

Available in

Code QAU-WPS-01

Size 1m x 100m (100m²)

Thickness 3mm

Code QAU-WPS-02

Size 1m x 16.5m (16.5m²)

Thickness 3mm