

# YOUNGMAN®

TRADE APPROVED SINCE 1926

YOUNGMAN  
TIMBER & ALUMINIUM

## LOFT LADDER RANGE



ACCESS YOUR UNUSED LOFT SPACE WITH  
THE IDEAL YOUNGMAN SOLUTION

# ECO S-LINE LOFT LADDER

150kg



EN14975

LOAD CAPACITY (Load includes user, tools, materials, etc.)



See our installation videos at [youngmanaccess.com/videos](http://youngmanaccess.com/videos)

Spring clip to secure sections when deployed

Requires no arc space for clearance or storage space in the loft; the ladder is stored within trapdoor

Insulated draught proof hatch

Handrail to aid safe climbing

Timber pull and push stowing pole included

Fits in UK standard 0.6m joist centres

OPTIONAL  
EXTENSION  
KIT AVAILABLE

Increases height to 3.51m

## SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height (m)	Hatch Casing Size L x W x D (m)	Sections x Treads	Weight (kg)
34535000	2.81	1.13 x 0.55 x 0.14	3 x 4	26.0

# TIMBERLINE LOFT LADDER

150kg



EN14975

LOAD CAPACITY (Load includes user, tools, materials, etc.)



See our installation videos at [youngmanaccess.com/videos](http://youngmanaccess.com/videos)

Folding timber loft ladder with a white-faced 26mm insulated trapdoor

High quality timber construction

Spring-assisted easy lowering and stowing

Slip-resistant treads and feet

OPTIONAL  
EXTENSION  
KIT AVAILABLE

Increases height to 3.50m.

## SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height (m)	Hatch Casing Size L x W x D (m)	Sections x Treads	Weight (kg)
34530300	2.80	1.13 x 0.55 x 0.12	3 x 4	23.0

# SPACEMAKER LOFT LADDER

150kg



BS EN14975

LOAD CAPACITY (Load includes user, tools, materials, etc.)



See our installation videos at [youngmanaccess.com/videos](https://youngmanaccess.com/videos)

Aluminium 2 section sliding ladder - ideal for occasional use

Fitted with wide, flat, slip-resistant treads

Unique shoot bolt fastening for safety and ease of use

## SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height (m)	Min. Floor to Loft Floor Height (m)	Min. Hatch Size (m)	Sections x Treads	Weight (kg)	Clearance in Loft (m)	
						Vertical	Horizontal
30234000	2.60	1.45	0.46 x 0.41	2 x 5	5.0	0.86	1.22



# EASIWAY LOFT LADDER

150kg



BS EN14975

LOAD CAPACITY (Load includes user, tools, materials, etc.)



See our installation videos at [youngmanaccess.com/videos](http://youngmanaccess.com/videos)

Pivot arm for smooth, gliding operation

3 compact sliding sections - ideal in restricted spaces

Handrail to aid safe climbing

Unique shoot bolt fastening for safety and ease of use

## SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height (m)	Min. Floor to Loft Floor Height (m)	Min. Hatch Size (m)	Sections x Treads	Weight (kg)	Clearance in Loft (m)	
						Vertical	Horizontal
31334000	3.00	2.30	0.51 x 0.43	3 x 4	7.0	0.75	1.05

# DELUXE 2 SECTION LOFT LADDER

## 150kg



BS EN14975

LOAD CAPACITY (Load includes user, tools, materials, etc.)



See our installation videos at [youngmanaccess.com/videos](http://youngmanaccess.com/videos)

Twin handrails for secure climbing

Solid design made from heavy duty aluminium

Deep and slip-resistant treads for comfort and security

Ladder attaches to loft hatch for easier loft deployment



### SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height (m)	Min. Floor to Loft Floor Height (m)	Min. Hatch Size (m)	Treads	Weight (kg)	Clearance in Loft (m)	
						Vertical	Horizontal
30634000	3.25	2.31	0.69 x 0.51	8 + 6	18.4	1.03	1.60

# TELESCOPIC LOFT LADDER

150kg



SAFETY  
TESTED

LOAD CAPACITY (Load includes  
user, tools, materials, etc.)



See our installation videos at  
[youngmanaccess.com/videos](https://youngmanaccess.com/videos)

Extra wide treads for  
comfort and security

Ideal for small hatches with  
minimal storage space

Adjustable to three lengths  
with automatic locking and  
release

Manufactured using  
anodised aluminium

No cutting required

## SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height (m)	Min. Floor to Loft Floor Height (m)	Min. Hatch Size (m)	Treads	Weight (kg)	Clearance in Loft (m)	
						Vertical	Horizontal
30100000	2.61	2.17	0.60 x 0.51	9	12.0	0.24	0.24
30100100	2.88	2.43	0.60 x 0.51	10	13.0	0.24	0.24



# LOFT LADDER RANGES

Code	34535000	34530300	3023400	31334000	30634000	30100000	30100100
Description	Eco S Line	Timberline	Spacemaker	Easiway	Deluxe	Telescopic 2.6m	Telescopic 2.9m
Material	Timber	Timber	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Min. Floor to Loft Floor Height (m)	-	-	1.45	2.30	2.31	2.17	2.43
Max. Floor to Loft Floor Height (m)	-	-	2.60	3.00	3.25	2.61	2.88
Max. Floor to Ceiling Height (m)	2.81	2.80	-	-	-	-	-
Min. Hatch Size (m)	1.13 x 0.55	1.13 x 0.55	0.46 x 0.41	0.51 x 0.43	0.69 x 0.51	0.60 x 0.51	0.60 x 0.51
Minimum Clearance Arc (m)	-	-	0.86	0.75	1.03	0.24	0.24
Minimum Length Behind Hatch (m)	-	-	1.22	1.05	1.60	0.24	0.24
Maximum Load Capacity (kg)	150	150	150	150	150	150	150
Loft Hatch and Trapdoor included	✓	✓	-	-	-	-	-
Trapdoor Insulation thickness (mm)	26	26	-	-	-	-	-
Casing size L x W x D (m)	1.13 x 0.55 x 0.14	1.13 x 0.55 x 0.12	-	-	-	-	-
Spring-assisted stowing	✓	✓	-	-	✓	✓	✓
Conforms to EN 14975	✓	✓	✓	✓	✓	-	-
Handrail	✓	-	-	✓	✓	-	-
Plastic feet	✓	✓	✓	✓	✓	✓	✓
Universal stowing Pole	✓	✓	✓	✓	✓	✓	✓
Timber Extension Kit	✓	✓	-	-	-	-	-

**Youngman®**

A WernerCo brand

Blackwater Trading Estate,  
The Causeway, Maldon,  
Essex, CM9 4LJ

01621 745 900

uk.customercare@wernereco.com

youngmanaccess.com

©2019 WernerCo. Rev. 10/19