



Aruba

In every sector from transport to retail, and in every environment from hotels and hospitals to schools and workplaces, Aruba is designed to meet all your project needs. Aruba is 100% recyclable to meet your sustainability targets.

Key Features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Enhanced acoustical absorption performance of 0.60 α_w for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Mix and match modules for increased flexibility and a more complete project solution
- Easy to handle and re-engineered for a better, easier fit
- Ideal for every space



Edge Detail	Board		Tegular24		Tegular15																							
Thickness (mm)	15		15		15																							
Modules (mm)	600 x 600 5460M 1200 x 600 5461M		600 x 600 5462M 1200 x 600 5463M		600 x 600 5464M 1200 x 600 5465M																							
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL/ XL ² Interlude HRC XL ² Silhouette XL ²																							
Colour	Global White																											
Sustainability	<div><div></div><div>44</div></div> <div></div> <div><div></div><div>A</div></div> <div><div></div><div>EN 13964 / E1</div></div> <div></div>																											
Acoustics	<div><div></div><div>EN ISO 354 & EN ISO 11654</div></div> <div><div></div><div>EN ISO 10848-2 & EN ISO 717-1</div></div> <table><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board, Tegular24, Tegular15</td><td>0.60</td><td>34 dB</td><td>C</td><td>0.55</td><td>0.35</td><td>0.45</td><td>0.60</td><td>0.60</td><td>0.60</td><td>0.60</td></tr></table>							α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular24, Tegular15	0.60	34 dB	C	0.55	0.35	0.45	0.60	0.60	0.60	0.60
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000																		
Board, Tegular24, Tegular15	0.60	34 dB	C	0.55	0.35	0.45	0.60	0.60	0.60	0.60																		
Fire Reaction	<div><div></div><div>Euroclass A2-s1, d0 EN 13501-1</div></div>																											
Performances & Features	<div><div></div><div>85%</div><div></div><div>95% RH</div><div></div><div></div><div><div></div><div>Lifetime Guarantee</div></div><div><div></div><div>30 Year System Guarantee</div></div></div> <div><div></div><div>3.6 Kg/m²</div><div></div><div></div><div></div><div>BIM READY</div></div>																											

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 133.1.05.23