

Ref. Code: AP053

Date: April 2016




## B Type Valley Trough

### Product Features

Corodrain valley troughs are a durable, economic alternative to lead. Corodrain B Type Valley Troughs fix over the batten for fast and simple installation. Meets all the requirements for the narrow valley troughs in NFRC Technical Bulletin 28.

- BBA Approved Cert No. 89/2153
- At least durable as lead
- Similar in appearance to lead
- Less prone to theft
- Quick to install
- UV light and acid rain resistant
- Smooth surface inhibits the growth of moss & lichen and build-up of debris
- Fire resistance to SAB to BS476 part 3 and Class 3 BS476 part 7

- Suitable for use on roofs with pitches from 17.5° to 55°
- Can accommodate a maximum difference between two rafter pitches of 15°
- Designed for use with natural slate, manufactured slate and plain tiles



SLATE VALLEY HB/BX

Product Specification	B type - Standard	BX type – Heavy Duty
Length and Code	3m – <b>HB30</b> , 2.4m - <b>HB24</b> , 1.8m - <b>HB18</b>	3m – <b>BX30</b> , 2.4m – <b>BX24</b>
Width	330mm	330mm
Standard Weight	1.83Kg/m <sup>2</sup>	2.4Kg/m <sup>2</sup>
Thickness	1.3mm	1.6mm
Colour	Grey/Blue	Grey/Blue
Material	GRP - High quality unfilled polyester resin with glass fibre reinforcement	GRP - High quality unfilled polyester resin with glass fibre reinforcement

### Valley Selection Table

RAFTER PITCH (degrees)	ROOF AREA LESS THAN 25m <sup>2</sup>		ROOF AREA 25 – 100m <sup>2</sup>		MINIMUM LAP LENGTH
	VALLEY TYPE	MAX. VALLEY LENGTH	VALLEY TYPE	MAX. VALLEY LENGTH	
17.5 TO 22	B / D	7.0m	—	—	350mm
22.5 TO 29	A / B / D	7.0m	B / D	14.5m	300mm
30 TO 34	A / B / D	7.5m	B / D	15.0m	200mm
35 TO 39	A / B / D	7.5m	B / D	15.5m	200mm
40 TO 44	A / B / D	8.0m	B / D	16.5m	150mm
45 TO 49	A / B / D	8.5m	B / D	17.0m	150mm
50 TO 55	B / D	9.0m	B / D	18.5m	150mm