



CROMASOL (WHITE/GREY)

Issue 4 – November 2008

Description:

Cromasol is a Superior, Brilliant White, Alcohol Based, Solar Reflective Coating and when applied to a variety of roofing substrates, provides lasting protection against UV degradation and solar heat gain. It is a ready to use product and should not be diluted.

It is specifically manufactured for use on Mastic Asphalt but is also suitable for use on BS747 Roofing Felts, fully cured and bituminous liquid roof coatings as used in remedial roof repair applications.

Cromasol does not attack bituminous substrates therefore will prevent softening of asphalt and Associated leaching into the drying film. The solvent-resin blend has been purposely chosen to ensure this.

The product is suitable for use on roofs susceptible to ponding, as Cromasol is capable to withstand complete immersion in water for long periods. Once applied it is completely water resistant (unlike water based reflective paints), even where conditions turn to rain before the film has cured.

Coverage Rates:

Coverage varies according to the type of surface. For smooth surfaces, a maximum coverage of 6m²/litre/coat is typical. For rough and uneven surfaces, coverage will reduce. Coverage rates may vary as a result of extreme changes in external temperatures.

Colour:

White/Grey

Surface Preparation:

All surfaces should be clean, dry and free from deleterious matter, dust and grit. Lichen and algae etc. should be removed using Moss & Mould Remover prior to the application of Cromasol. Surfaces should be structurally sound and any blisters in existing felt should be split, dried and rebonded and sealed. Heavily oxidised bituminous surfaces as well as porous or friable surfaces should be primed with one coat of Cromar Bituminous Primer, after which they must be left until hard and free from solvents. Before applying Cromasol, newly applied asphalt and other bituminous surfaces should be allowed to weather for a period of 2-3 days. For existing mineral or rough surfaces, greater attention to dirt removal should be paid due to difficulties in dislodging dirt and organic growth. It is essential that roof surfaces that pond are thoroughly cleaned.

Application Instructions:

Apply Cromasol when the surface to be treated is dry and both surface and ambient temperatures are between 5°C and 35°C. Before applying, ensure the contents of the containers are thoroughly mixed, as failure to do this may result in an uneven appearance. Mix regularly throughout application. Apply by roller or airless sprayer, two coats of Cromasol to the prepared surface, allowing drying overnight between each application. Where possible, the second coat should be applied at right angles to the direction of the first coat. The coating may also be applied by brush, however extra care must be taken, as heavier applications often tend to occur.

To maintain optimum performance we recommend re-coating approximately every 5-7 years depending on atmospheric conditions.





Technical Data Sheet

- Cleaning Tools:** Tools may be cleaned using White Spirit.
- Container Sizes:** 5kg, 20 kg
- Storage:** Cromasol should be stored in dry conditions away from direct sunlight and sources of ignition. Temperatures should be between 8°C-25°C. Part used containers should be tightly re-sealed.
- Health & Safety:** Please refer to Health and Safety Data Sheet on Cromasol.
- Further Information:** In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products' are available for sale in accordance with Cromar's Standard Terms and Conditions of Sale, which are available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our Representatives, Agents, or Distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Unit 3, The Maltings Industrial Estate
Doncaster Road, Whitley Bridge
North Yorkshire DN14 0HH
Tel: 01977 663133 Fax: 01977 662186
info@cromar.uk.com www.cromar.uk.com



CROMAR
BUILDING PRODUCTS LIMITED