



MORTAR? LEAVE IT OUT!

When it's got to be DRY only "High and Dry" will do!

A truly simple and universal Dry Fix Ridge System



Easy and quick
to install

Whatever the weather

No cost premium
for ventilation



- ✔ A truly universal system to suit half round, angle and universal angle ridge.
- ✔ Suitable for use on all types of tile or slate roofs.
- ✔ No cost premium for ventilation due to unique patented designs.
- ✔ Simple and quick to install providing an accurate and secure ridge line easily achieved using the innovative Uni-Ridge Fixing Clip.
- ✔ Cost effective and any surplus components are usable on the next installation.
- ✔ Building Research Establishment Tested.

Why choose anything else?

forget the weather...

...fit the Hambleside Danelaw Universal Dry Fix Ridge DFR3





DFR3 Universal Dry Fix Ridge 3 Linear Metre Pack

Uni-Ridge Gasket

A truly universal joining gasket made from recyclable low-density polyethylene to suit different sizes of ridge tile and easily trimmed if necessary. The flexible gasket incorporates double water channels and integral screw fixing seal for a high level of watertight security. The result of this unique design is a more aesthetically pleasing and discreet ridge joint.



Uni-Fixing Clip

The Uni-Fixing Clip is designed to be fitted in either of its two positions to suit different ridge heights and roof pitches. Made from durable and recyclable polypropylene it is non-corrosive unlike other galvanised strap systems and very easily adjusted for position as required. By avoiding the commonly used stacked ridge battens, the clip enables a secure and stable ridge fix facilities accurate ridge tile alignment.



Uni-Vent Strip

Made from robust recyclable polypropylene, the slim line appearance of the Uni-Vent Strip provides an aesthetically discreet finish to the ridge line. A clear air path is provided in accordance with regulation requirements along the 750mm lengths of ventilator. Successive lengths of vent are joined with an expansion link for accurate positioning and continuity. The Uni-Vent Strip is self-aligning and incorporates surface guidelines for simple ridge tile alignment.



Uni-Filler Strip

Universal to all profiles of tile, the 755mm lengths of Uni-Filler Strip are butt jointed to provide a continuous barrier to bird access, nesting and build up of wind debris and snow. Made from recyclable low-density polyethylene, a closed cell foam seal incorporated in the strip to provide extra weather tight security at the head of profiled tiles. This seal, with the comb section removed, is utilised on the surface of flat, plain tiles and slates to conform to the surface shape e.g. double cambers on plain tiles and riven slate surfaces, for superior resistance to water penetration.

