

Allweather was specifically designed to address the issue of unpredictable wet weather conditions. Its unique formula means that unlike other products Allweather can be applied to wet surfaces, during rain and down to 0°C. With added fibres Allweather eliminates the need for detailing tape and can be applied to all surfaces without the need for primer.

As a cold applied one coat system Allweather offers a simple to use rapid solution for waterproofing during rain.

Preparation

Remove all loose material and loose chippings by scraping or power wash.

Brush off ponding water, however wet surfaces are not a problem for application as Allweather can be applied directly to wet surfaces.

Any surface areas contaminated by moss, algae growth or lichen must be treated with a proprietary fungicidal wash prior to application in accordance with its data sheet.

Any cracks and gaps should be raked out to remove dirt build up.

Any silicone substrates or silicone sealants should be removed prior to the application and re-applied if necessary on completion.

Any ice present on the surface in cold conditions must be removed as well as any oil or grease

Weather conditions

Due to its unique formula Allweather waterproof membrane can be applied during rain and down to 0°C as long as the surface is free from ice or frost.

Allweather can be applied to any substrate and fully bonds without the need for primer.

Detailing

Allweather is a single product system containing fibres, allowing it to be used across the entire substrate, eliminating the need for reinforcement or detailing tape. Simply apply directly to up-stands and vertical surfaces using a paint brush. For smaller cracks or holes apply directly to surfaces, for larger voids which can not be bridged, we recommend Allweather Emergency Repair or alternatively a heavy duty adhesive tape maybe required, (apply the tape and apply product directly over the tape). Note: additional material may be required for joints and upstands and 90° angles.

Main application

For optimum performance Allweather should be applied in a single coat. To avoid pinholing apply by brush using a forwards, backwards and side to side motion. work your way off the roof towards a suitable exit.

Coverage: 1KG will cover 1m² - 2m² (depending on surface condition) DO NOT THIN PRODUCT.

Upon application Allweather provides an immediate waterproof seal and as such will not be affected by rain during or immediately after application. Product may take several days to fully cure.

Allweather is specifically designed for exterior roof waterproofing and is not recommended for internal use or for use in fishponds. All above instructions are guidelines only, for full details visit our website or call us on 08443 356 386

Storage

Store between 5°C and 30°C, use within 2 years.

STIR THOROUGHLY BEFORE USE