

EVERBUILD 405 PATH & PATIO SEAL



| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|-----------|---------|
| Clear | PAT5 | 5Ltr | 4 |
| | PAT25 | 25Ltr | 1 |

Product Description

EVERBUILD PATH AND PATIO SEALER is a solvent free acrylic coating used to seal and protect patios, paths, natural stone, concrete and block paving from the effects of the sunlight, water, oil, petrol and fungal/moss growth. The milky solution dries to hard wearing water repellent film which gives a low sheen slip resistant finish which will reduce dirt pickup and facilitate easier cleaning. The product is safer to use than conventional solvent based products, i.e. it is non-flammable and will not harm plants and animals when used as directed.

Benefits

- Solvent free formulation – non-flammable, low odour.
- Improves appearance of dull paths/stone.
- Also acts as a dustproofer and facilitates easier cleaning.
- Dramatically improves water and mar resistance - High degree of water repellency in dried film.
- Contains a powerful fungicide – prevents unsightly mould growth.

Areas For Use

- Seals and protects, paths, patios, natural stone, concrete and block paving from the effects of the sunlight, water, oil, petrol and fungal/moss growth.

Limitations

- Use only as directed. Store only in original container.
- Do not use on surfaces which have been treated with silicone or stearate based water seals (eg WATERSEAL) unless the surface is weathered enough so as to show no water beading effects.
- Do not use if rain is imminent (within 5 hours at 20°C).
- Do not apply below 5°C (air or surface temp).
- Dispose of this product and packaging correctly. Do not allow to enter watercourses. It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

Surface Preparation

Surfaces must be free from grease, dust, loose material, algae etc. Clean surfaces with EVERBUILD MOSS AWAY. For bad oil stains, use a proprietary detergent and hot water. For very badly soiled surfaces, use EVERBUILD BRICK AND PATIO CLEANER. In all cases, wash down the cleaned surface

with a hose and broom to remove all traces of cleaning product. All artificial stone (cement based) and all block pavers must be left for three months minimum after placing before over coating with this product. This will allow salts to leach out which otherwise may cause unsightly white patches appearing beneath the sealer, especially when the patio is wet.

Application

Stir well before use. May be applied to damp (but not wet) surfaces. Apply using a long pile roller and tray or low-pressure spray. Ensure even and thorough coverage, especially on textured finishes where ponding of the material must be avoided. Apply in two coats, allowing 2 hours between coats. An extra coat may be applied if a semi gloss finish is required. Drying time will be 4 hours from last coat at 20°C. This will be extended at lower temperatures. Do not apply below 5°C.

Areas treated with this product can be cleaned with warm water and detergent or EVERBUILD MOSS AWAY. Do not use acid based cleaners, as these will remove/discolour the product. Avoid using power washes.

Specific Data

| | |
|--------------------------------|--|
| Appearance | Clear solution (water based) |
| Specific Gravity @ 20°C | 1.05 g/cm ³ |
| M.F.F.T | 5°C |
| Solids | 16% w/w |
| Drying Time | 4 hours |
| Coverage | 1 Litre will cover approximately 8m ² per coat depending on nature of surface |

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers. PROTECT FROM FROST.

Shelf Life

12 months when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.