




everyday


## *flexi* everyday - *flexi* H-frame kits

**H-frame kits to support ducts, pipes and electrical containment**



### Features & Benefits

- Non-penetrative support
- Flexible design to accommodate late design changes
- Fast and simple installation
- Hot dip galvanised bracketry
- Rubber mats adhered to feet
- Three foot sizes available
- The kit comes supplied in a box
- Full AutoCAD drawing support
- Load management and wind calculations available
- Full on-site support and surveying services



Pump House  
Glaisdale Drive East  
Nottingham  
NG8 4LY  
Tel: 0115 900 5858  
[www.flexisupportsystems.co.uk](http://www.flexisupportsystems.co.uk)  
[sales@flexisupportsystems.co.uk](mailto:sales@flexisupportsystems.co.uk)



light



heavy



access



solar




## flexi H-frame kits

Our H-frame kits offer the installer full flexibility by providing a solution where they can supply their own strut to suit their installation requirements. The H-frame kits are supplied with a pair of either our 320mm feet, most widely used in the majority of installations or where heavier more demanding loads are present, then our 500mm foot version kit is available. All kits are supplied with hot dip galvanised angle brackets together with all the necessary fixings to assist the installer in a low cost, versatile and fast assembly solution on site.

### Typical duct installation



### What's in the box



Part Code - F-HF-320 (shown above)

Part Code	Description	Foot Size	Recommended Max Load	Weight
F-HF-320	Flexi H Frame Set - 2 square black feet and fittings	320 mm x 320 mm	250 kg	4 kg
F-HF-500	Flexi H Frame Set - 2 square black feet and fittings	500 mm x 500 mm	600 kg	6 kg



### Specification Extract

Duct/pipe/tray services will be supported on flexi everyday H-frame kits utilising (add required foot size) and with adhered rubber mats. Contact Pump House: 0115 900 5858

### Application

Suitable for everyday installation of ductwork including associated attenuators. Small to medium sized flow and return pipework and electrical containment e.g. cable trays or cable ladders.

### Material Specification

- Foot - 320mm & 500mm square UV stabilised 90% polypropylene, 10% grp
- Mat - 100% natural rubber, (mat is adhered to the feet)
- Fixings - M10 ZP sets, sprung washers and nuts.
- Angle brackets - mild steel, hot dip galvanised BS EN ISO 1461:1999
- This product is supplied boxed. Kit does NOT include strut (frame) metalwork.

### Our service offers you

- Quotation upon request
- Full AutoCAD drawings support
- Site support and site surveys
- Load management calculations
- 20 years experience in flat roof design and providing support systems to building services
- Fast delivery
- Experienced in-house technical staff
- Friendly, family run business