DoP Nº: TDS/1417

Edition: November 2016 Issue 01 Revision 0



Declaration of Performance

In accordance with Regulation (EU) No 305/2011;

1 Unique identification code of the product-type

1. Unique identification code of the product-type						
Product Name						
	Monarperm Breathe One					

2.	Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4)	See product label	
3.	Intended use	Underlays for discontinuous roofing and walls	
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)	Icopal Limited Barton Dock Road, Manchester, M32 0YL. United Kingdom Production location ref: S0001-01-101	
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2)	Not relevant	
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3	
7.	In case of the declaration of performance concerning a Construction, product covered by a harmonised standard	Determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system AVCP 3 was carried out by notified body No. 1434	
8.	In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued	Not relevant	

9. Declared Performance

Essential Characteristic	Performance	Tolerance	Units	Harmonised technical specification
Reaction to fire	Class E	-	-	EN 13859-1 EN 13859-2
Watertightness	W1	-	-	
Tensile Strength	MD: 190 TD: 100	±40 ±40	N/50 mm	
Elongation	MD: 80 TD: 90	±20 ±20	%	
Resistance to Tearing	MD: 100 TD: 100	±20 ±20	N	
Flexibility at Low Temperature	≤ -30	-	°C	
Dangerous Substance	NPD	-	-	
Durability (after aging):				1
Watertightness	W1	-	-	
Tensile Strength	MD: 130 TD: 70	±30 ±20	N/50 mm	
Elongation	MD: 55 TD: 60	±20 ±20	%	
MD = Machine Direction. TD =Transverse	Direction. NPD = No Perform	ance Determined.	•	•

Signed for and on behalf of the manufacturer by:

Neil Harrison

Position: Technical Director Place: Manchester, UK Date: 04 November 2016

. (signature)