



THE HANBURY RANGE



The Hanbury clay roof tile is one of the last few genuinely handmade clay roof tiles still available in the UK today.

Using fine, rich British clay, each Hanbury tile is crafted to the highest standards. Its individuality, warmth and character re creates the heritage and traditional appearance of bygone years.

Available in a variety of shades and blends, the Hanbury range is ideal for new build, renovation or restoration projects. Manufactured using traditional skills and methods combined with the latest in kiln technology, the Hanbury tile meets all the British Standard requirements for clay roofing tiles.



HANBURY APPLEDORE

Rich red in colour, a great choice for complementing the darker tones of Honeywell, Burmarsh and Churchland.



HANBURY CHURCHLAND

An ideal choice for renovation and restoration works. With its deep dark tone, this shade will work alongside original tiles and is perfect for complete re roofs.



HANBURY BURMARSH

The perfect choice for restoration and new build properties when an instant weathered look is required.



HANBURY HONEYWELL

A mellow and subtle shade of brown that gives an instant settled look perfect for new build and restoration projects that need to match in with local buildings and surroundings. A popular choice for oak framed houses.

TECHNICAL INFORMATION



✓ 30 YEAR
GUARANTEE



SPECIFICATION FOR HANBURY TILES

TECHNICAL DATA	ROOF	VERTICAL
Headlap	65mm	38mm
Minimum pitch	35°	75°
Batten spacing at maximum gauge	100mm	114mm
Size of tile	265 x 165mm	265 x 165mm
Covering capacity	60 tiles per m ²	53 tiles per m ²
Cover width	165mm	165mm
Weight as laid	72kg per m ²	63.6kg per m ²
Battens per m ²	10m	8.8m
Batten size - up to 450mm after centres	38 x 25mm	38 x 25mm
Batten size - up to 600mm after centres	38 x 25mm	38 x 25mm
Nail size / type for tiles	38 x 3.35mm aluminium ring shank clout head	38 x 3.35mm aluminium ring shank clout head

RECOMMENDATIONS

- Tiles to be laid in accordance with BS 5534
- Tiles laid to be drawn from a minimum of 3 separate pallets to ensure best effect
- Tiles are delivered on non returnable shroud wrapped pallets
- Pallets on site should be on firm, dry and level ground, no more than two pallets high
- Due to limitations of the print process, colours should be selected from actual samples



If you would like further information please contact us on:

Kent Clay Tiles Ltd, Mountfield Road, New Romney, Kent, TN28 8LH

T 01797 364777 E sales@kentclaytiles.co.uk W www.kentclaytiles.co.uk