




One Hour Fire Rated Drop Down Loft Access Door

CODE GL 280 F

CODE GL 281 F



Note: GL281F Includes a Euro Key Lock

Description

The **GL 280 F** Drop Down One Hour Fire Rated Loft Access Door is designed to be flush fit to the ceiling and to fit between 600mm centre trusses. The modern design fits in with almost all house decor styles. Finished with a light texture, the door can be easily cleaned with a solvent free, damp cloth, or alternatively can be painted to match the surrounding decor.

Draught seals are located to all 4 sides of the door and seal to the frame complete with latch (euro lock GL 281 F) preventing the problem of moist, warm air entering the roof space.

The Fire Rated Loft Door (GL 280 F) comes with a budget lock and 'T' key as standard, or can be supplied with a euro lock (GL 281 F).

The product can be used in conjunction with Manthorpe's **GL 256** and **GL 257** (see Tech sheet 8187) Loft Access Ladder.

The GL280 F fire rated access door met the British Standard recommendation for a leakage rate of <1m³ at a pressure differential of 2 Pa, and the Building Regulations Part L2A 'reasonable limit' for the design air permeability of buildings of 10m³/h.m² at 50Pa.

References

BRE	Digest 262/270
BSI	BS5250
DOE	Building Reg L1, L2
NHBC	Good Practice Guide
NHBC	Standards 7.7
BS	476: Part 22
WFRC	157180

Specification	
Packing Details	Individually Packaged In Cardboard Box
Material	Zintec Electro Galvanised Mild Steel Finished in polyester Powder Coat (White)
Box Weight	10 Kg
Seal	PVC Foam
Insulation	Mineral Fibre