## manthorpe building products

## **Product Information Sheet**

## Tile Ventilator Range - Plain Tile

CODE GTV-PT

### **Description**

The Manthorpe in-line plain tile ventilator is designed to provide a quick and simple solution to the problems of roofspace ventilation and mechanical extraction / soil stack termination through a plain tiled roof. The vent is quick and easy to install, taking the place of a 3 plain tiles with no need to cut the battens. The in-line profile helps to maintain an unbroken appearance to the roofline whether used at high or low level.

The tortured path through the internal weathering geometry is designed to maintain a constant airflow gap of 7,000 mm² whilst channelling any water ingress out of the vent and on to the roof covering below, with the 4mm louvred grill and placed to prevent the entry of debris and large nesting insects.


Available in a range of four colours to suit most styles of concrete and traditional clay plain tiles from all major UK and Irish tile manufacturers.

For use with mechanical extraction or soil stack / vent pipe termination; the GTV-AD Flexi Pipe Adaptor and GRPA Flexible Pipe range should be used. For detailed fitting instructions see MBP-0968, and for mechanical extraction fitting details see MBP-8292.

Weight	0.78kg
Box Qty	6 (5.25kg per box)
Materials - Top	PVC
Base	Polypropylene
Colours	Terracotta, Grey,
	Brown & Antique Red
Manufacturing	Injection Moulded
Free Airflow	7,000 mm² per unit

#### **Features**

- In-line and discreet low profile design.
- 4mm louvred flyscreen grill.
- No batten cutting required.
- Range of colours available.
- Suitable for concrete and traditional clay tiles.
- Profiles suit all top tile manufacturers.
- Fully independently wind tunnel tested.
- Base outlet feeds directly into roof space.
- Adaptor available for mechanical extraction.
- Suitable for use down to a 35° roof pitch.



MANTHORPE BUILDING PRODUCTS LTD MANTHORPE HOUSE BRITTAIN DRIVE

DE5 3ND

CODNOR GATE BUSINESS PARK RIPLEY

**DERBYSHIRE** 

TEL: 01773 514 200 FAX: 01773 514 262 EMAIL:

sales@manthorpe.co.uk WEB

www.manthorpe.co.uk

DRN B.H.

without notice.

Date 25.01.13

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification

MBP 8307

DRG No

Issue

**A** 1 of 2

# manthorpe building products


### **Product Information Sheet**

### Tile Ventilator Range - Plain Tile

CODE GTV-PT

48mm

26mm



Required Ventilation	Vent Spacing
5,000 mm²/m	Install at 1.4m centres
10,000 mm²/m	Install at 0.7m centres
25,000 mm²/m	Install at 0.28m centres

### References

BSI: BS 5250:2002 Control of Condensation in Building BSI: BS 5534:2003 Code of Practice for Slate and Tiling BSI: BS 490:2004 Concrete tiles and fittings for roof covering

BRE: prEN 15601


**Building Regulations 2010** 

NHBC: Good Craftsmanship Guides

#### **Installation Overview**

The vent tile is laid in a broken bond format, taking the place of 3 individual plain tiles across 2 courses.

Once the position of the vent is marked, the underlay can be cut to allow for the base outlet, at which point the unit can be aligned with the tile course below and nailed in place. Tiling can then be resumed, fitting the adjacent tiles around the vent.



The vent outlet is designed to penetrate through the roofing underlay between the tile courses, meaning there is no need to cut or trim the battens, even when laid at the lowest batten gauge of 88mm (when using 38mm roofing battens).

NOTE: When using the vent for mechanical extraction, the pipe adaptor is fitted from inside the roof space.

MANTHORPE BUILDING PRODUCTS LTD

MANTHORPE HOUSE BRITTAIN DRIVE

CODNOR GATE BUSINESS PARK

RIPLEY

DERBYSHIRE DE5 3ND

TEL: 01773 514 200 FAX: 01773 514 262

EMAIL:

sales@manthorpe.co.uk

WEB

www.manthorpe.co.uk

DRN B.H.

without notice.

Date 25.01.13

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification

DRG No

Issue

**MBP 8307** 

**A** 2 of 2