Technologies

pavatex

PAVADENTRO Internal woodfibre insulation



- Vapour barriers can be omitted thanks to an innovative, vapour-controlling functional layer
- Comfortable living environment thanks to moisturebuffering and capillary properties
- Outstanding healthy living through natural system components of woodfibre and clay or lime renders
- Harmonious renovation solution for facades worthy of preservation

Delivery form

hickn. [mm]	Weight [kg/sqm]	Format [cm]	Board dim. [cm]	Number of boards	per pallet [sqm]	per pallet [kg]	Edge profile
40	7.00	102 x 60	101 x 59	100	61.20	446	Tongue & Groove
60	10.50	102 x 60	101 x 59	68	41.62	455	Tongue & Groove
80	14.00	102 x 60	101 x 59	48	29.38	429	Tongue & Groove
100	17.50	102 x 60	101 x 59	40	24.48	446	Tongue & Groove

Field of application



PAVATEX soffit board

Thickn. [mm]	Weight [kg/sqm]	Weight [kg/package]	Format [cm]	Number of boards/ package boards/ palett	per packa- ge/ palett [sqm]	per pallet [kg]	Edge profile
20	3.60	20.70	120 x 60	8/96	5.76 / 69.12	264	Flat
40	7.20	20.70	120 x 60	4 / 48	2.88 / 34.56	264	Flat

Technical data

	Bulk density ρ [kg/m³]	175					
	Thermal conductivity (EN 13171) λ_D [W/(mK)]						
	Specific heat capacity C [J/(kgK)]						
	Fire behaviour (EN 13501–1)						
	Compressive stress at 10% compressive deformation [kPa]	70					
	Tensile strength perpendicular to plane of board [kPa]	5					
	Waste code according to The European Waste Catalogue (EWC) 030105;	170604					
	Identification code WF-EN13171-T5-CS(10\Y)70-TR5	-AF100					
	s _d value [m] (40/60/80/100 mm) 0.65 /0.75/0.8	35/0.95					

Product description

PAVADENTRO is an innovative, ecological internal insulation. It actively exploits capillary conductivity and the hygroscopic properties of woodfibres to prevent the formation of damaging moisture. In addition, the green functional layer, specially developed by PAVATEX, ensures controlled moisture transfer. It is fixed with brackets or insulation anchors to the full-surface base. It is coated with natural render systems based on clay and lime renders.

Full declaration

For further information see MSDS on www.pavatex.com

Storage

Store dry and protected from damage. Only install when dry. Stack no more than 4 pallets on top of one another.





