



PHOTONFOIL

Data sheet

Product code P33

| Technical Data | | | |
|----------------------|--------------------------------|---|----------------|
| Width (effective) | 1200 | mm | EN 822 |
| Flap | 50 | mm | EN 822 |
| Yield | 12 | m ² | |
| Thickness | 33 | mm | EN 823 |
| Weight | 0.95 | kg/m ² | |
| Core R value (90/90) | 0.97 | W/m.k | EN 16012 |
| Emissivity (90/90) | Measured 0.02 Declared 0.05 | | EN 16012 |
| Vapour barrier | >6,000 | MN.s/g.m | EN 12572 :2001 |
| Air barrier | Practically zero | m ³ /h.m ² @ 100 Pa | EN 9237 |
| Fire performance | Class E | | EN 11925-2 |

| Packaging Data | | | |
|------------------|-----|----|--|
| Roll length | 10 | m | |
| Roll diameter | 400 | mm | |
| Roll weight | 12 | Kg | |
| Rolls per pallet | 18 | | |

Thermic Technology Limited
Moorland Gate Business Park
Chorley
PR6 9FE

Tel: 01257 241084
Fax: 0161 883 1340

www.photonfoil.co.uk
info@thermictechnology.co.uk

Issued September 2015