

PROTOR BITUM - AEROSOL - 7272 A

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : PROTOR BITUM - AEROSOL

Product code : 7272 A.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Bituminous product for sealing

Indoor, use within the framework of the repair.

1.3. Details of the supplier of the safety data sheet

Registered company name : ORAPI.

Address : PARC INDUSTRIEL DE LA PLAINE DE L'AIN - 225 ALLEE DES CEDRES.01150.SAINT-VULBAS.FRANCE.

Telephone : 33-(0)4-74-40-20-20. Fax : 33-(0)4-74-40-20-21.

fds@orapi.com

1.4. Emergency telephone number : 33-(0)1-45-42-59-59.

Association/Organisation : INRS .

Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Extremely flammable (F+, R 12).

Vapours may cause drowsiness and dizziness (R 67).

Aquatic environmental hazard, chronic toxicity: toxic (N, R 51/53).

2.2. Label elements

Mixture for aerosol application.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Dangerous for the environment

Extremely flammable

Risk phrase :

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 12 Extremely flammable.

R 67 Vapours may cause drowsiness and dizziness.

Safety phrase :

S 16 Keep away from sources of ignition - No smoking.

S 2 Keep out of the reach of children.

S 29 Do not empty into drains.

S 46 If swallowed, seek medical advice immediately and show this container or label.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

S 23 Do not breathe spray.

S 24 Avoid contact with skin.

S 51 Use only in well-ventilated areas.

S 61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROTOR BITUM - AEROSOL - 7272 A

2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006.

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
CAS: 1317-65-3 EC: 215-279-6			[1]	10 <= x % < 25
CALCAIRE				
EC: 919-446-0 REACH: 01-2119458049-33	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066	Xn,N Xn;R65 N;R51/53 R10 R66-R67		10 <= x % < 25
HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)				
EC: 931-254-9 REACH: 01-2119484651-34	GHS07, GHS09, GHS08, GHS02 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	Xn,N,F Xn;R65 Xi;R38 N;R51/53 F;R11 R67		10 <= x % < 25
HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE				
CAS: 811-97-2 EC: 212-377-0 REACH: 01-2119459374-33	GHS04 Wng 280.		[1]	10 <= x % < 25
1,1,1,2-TETRAFLUOROETHANE				the mixture an
CAS: 64742-95-6 EC: 265-199-0 REACH: 01-2119455851-35	GHS09, GHS08, GHS07, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066	Xn,N Xn;R65 Xi;R37 N;R51/53 R10 R66-R67	P	2.5 <= x % < 10
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.				
INDEX: 601-025-00-5 CAS: 108-67-8 EC: 203-604-4	GHS02, GHS07, GHS09 Wng Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411	Xi,N Xi;R37 N;R51/53 R10	[1]	0 <= x % < 2.5
MESITYLENE				
CAS: 109-28-4 EC: 203-661-5	GHS07, GHS09 Wng Eye Irrit. 2, H319 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	Xi,N Xi;R36 N;R50/53		0 <= x % < 2.5
9-OCTADECENAMIDE N-(3-(DIMETHYLAMINO)PROPYL)-(9Z)-				

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

PROTOR BITUM - AEROSOL - 7272 A

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

Consult a physician in case of disorder.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any pain, redness or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove clothing impregnated and wash carefully the skin with some water and some soap or use a known cleaner.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- various hydrocarbons
- aldehyde

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

PROTOR BITUM - AEROSOL - 7272 A

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non fire-fighters

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For fire-fighters

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

PROTOR BITUM - AEROSOL - 7272 A

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
108-67-8	100	20	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
108-67-8	25 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
811-97-2	1000 ml/m3	4200 mg/m3	8(II)	DFG, Y
108-67-8	20 ml/m3	100 mg/m3	2(II)	DFG, EU, Y

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1317-65-3	-	10	-	-	-	-
108-67-8	20	100	50	250	-	84

- Switzerland (SUVA 2009) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Temps :	RSB :
1317-65-3	3 a	-	-	-	-	-
811-97-2	4200	1000	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
811-97-2	1000 ppm	-	-	-	-
108-67-8	25 ppm	-	-	-	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

PROTOR BITUM - AEROSOL - 7272 A

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	viscous liquid. spray.
------------------	---------------------------

Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	<= 35°C
Vapour pressure (50°C) :	not relevant.
Density :	1.08
Water solubility :	Insoluble.
Melting point/melting range :	not relevant.
Self-ignition temperature :	not relevant.
Decomposition point/decomposition range :	not relevant.
Chemical combustion heat :	not specified.
Inflammation time :	not specified.
Deflagration density :	not specified.
Inflammation distance :	not specified.
Flame height :	not specified.
Flame duration :	not specified.

9.2. Other information

Colour : black

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- flames and hot surfaces
- accumulation of electrostatic charges.
- sources of ignition

PROTOR BITUM - AEROSOL - 7272 A

10.5. Incompatible materials

Keep away from :

- strong acids
- oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- various hydrocarbons
- aldehyde

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

Acute toxicity :

HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE

Oral route : DL50 > 5000 mg/kg
Species : Rat

Dermal route : DL50 > 3000 mg/kg
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route : LC50 > 20 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Oral route : DL50 > 15000 mg/kg
Species : Rat (recommended by the CLP)
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : DL50 > 3400 mg/kg
Species : Rat (recommended by the CLP)

Inhalation route : LC50 > 13100 mg/m³
Species : Rat (recommended by the CLP)
OECD Guideline 403 (Acute Inhalation Toxicity)

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

PROTOR BITUM - AEROSOL - 7272 A

12.2. Persistence and degradability

12.2.1. Substances

HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2013).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

PROTOR BITUM - AEROSOL - 7272 A

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327 344 959	E0

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 75/734/CEE modified by directive 2013/10/UE
- Regulation EC 1272/2008 modified by regulation EC 618/2012

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Title for H, EUH and R indications mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
R 10	Flammable.
R 11	Highly flammable.
R 36	Irritating to eyes.
R 37	Irritating to respiratory system.

PROTOR BITUM - AEROSOL - 7272 A

R 38	Irritating to skin.
R 50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).