

PRODUCT DATASHEET

RPA Self-Levelling Adjustable Paving Pedestal

RPA self-levelling adjustable paving pedestal supports all types of calibrated paving.



- Provide consistent spacing between slabs
- Pre-installed snap-off design allows for easy removal as required.



'Ball and socket' floating head design allows slope correction of up to 10.5% (60). No levelling shims are required - see self-levelling concept diagram.

ADJUSTABLE THREADED SECTION

Easily allows millimetre perfect adjustment within given range.


HEIGHT EXTENSION COLLAR

- Easy to attach with single 'click' motion
- Builds up pedestal height in 100mm increments.

WIDE SUPPORTING BASE

- Evenly spreads load
- Protects membranes
- Water drainage holes prevent moisture build-up
- Holes enable pedestals to be fixed to surface if required.







Self-levelling diagram.

TECHNICAL SPECIFICATION

Material	PP Polypropylene (recyclable), UV resistant
Biological/chemical	Resistant to moulds, algae, alkali, bitumen
Height range	40-56mm, 50-70mm, 70-110mm, 110-160mm, 150-210mm, 200-300mm, 300-400mm, 400-500mm, 600-700mm, 700-800mm, 800-900mm, 900-1000mm
Compression	2100kg (certified compression data available on request)
Base Diameter	210mm / 220mm
Head Diameter	130mm
Spacer tab thicknesses	2mm / 4mm (standard) / 6mm
Working Temperature	-40°C to 120°C



Castle Way Ellon AB41 9RG

01358 726005 sales@rynosupport.com rynosupport.com

© Copyright Ryno Ltd 2016