














Tact Tiles  
multi functional flooring

## TECHNICAL INFORMATION



## BRIQ

Material:		ISO2076	Environmentally friendly recyclable UV-stabilized polypropylene.
Size of tile:		EN427	377.2 x 377.2 mm. 1 m <sup>2</sup> / box = 7 tiles. 5 m <sup>2</sup> / box = 35 tiles.
Thickness of tile:		EN428	10.1 mm.
Weight:		EN430	1 tile: 0.366 kg. 1 m <sup>2</sup> : 2.272 kg. 5 m <sup>2</sup> : 13.4 kg.
Point load:		QUALIFIED TEST BY BERGO	250 ton / 1 m <sup>2</sup> = 2500 kg/dm
Light fastness:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
UV-stability		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance:		SSEN-13893	>0.3
Impact resistance:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m <sup>2</sup> / -20 °C = 5 kJ/m <sup>2</sup> C15 kJ/m <sup>2</sup>
Fire category:		EN ISO 11925-2	E <sub>n</sub>
CE certification:		EN 14041	0402-CPD-P605080A



By normal use and treatment  
the material guarantee time  
is 10 years.



Bergo Flooring AB fulfills the  
requirements of ISO 9001.



Bergo Floors are  
100% recyclable.



The Bergo Tile - Polypropylene floor  
covering for use out- and indoors.  
Reaction to fire Class E<sub>n</sub>.  
Slipiness DS.



SYSTEM  
2

