

Step Repair Mortar

Description

Adawall Step Repair Mortar is a rapid hardening mortar for repairing damaged kerb stones.

Advantages

- Easy to use
- Requires no specialist skills or tools
- Repairs can be carried out quickly
- Can be applied in most weather conditions
- Supplied prepacked for mediate use

Composition

Adawall Step Repair Mortar is a polymer modified mortar supplied in a 5kg waterproof pail. Inside is 5kg of premixed powder requiring the addition of 2.72 litres of clean potable water.

Mixing the Adawall Step Repair Mortar

- Open the pack of powder and empty into the mixing vessel
- Add enough water to powder to give a workable mix
- Mix by hand or use a slow speed stirrer
- Do not mix more than can be applied within the working life of the mortar (generally 5-10 minutes depending on temperature)
- A trowelling mortar consistency will not bleed or shrink

Application Procedure

- The minimum application depth for Adawall Step Repair Mortar is 2mm
- The surface must be clean and structurally sound
- Avoid 'feather edging' by cutting out the repair area
- Damp the surface with clean water
- Whilst the surface is damp apply the mixed Adawall Step Repair Mortar
- Apply by hand and finish with a float or trowel to achieve the required profile
- The material will be strong enough to withstand impact after 1-2 hours
- When applying material in extremely warm or cold temperatures, the working life and initial 'set' will be affected