



Product Description

FEB AQUASEAL FLASHING AND ROOF PRIMER is a priming solution designed to deeply penetrate and seal porous surfaces to provide a base for bituminous water proofing and flashing systems.

FEB AQUASEAL FLASHING AND ROOF PRIMER is a blend of high quality bitumen's and hydrocarbon solvents. It contains a wetting agent to enable it to be applied to 'damp' as well as dry surfaces.

Typical Uses

FEB AQUASEAL FLASHING AND ROOF PRIMER is used prior to the application of a wide range of other Aquaseal products. Applied to porous substrates, it seals and improves the adhesion of Aquaseal waterproofing and flashing systems which include:

- FEB AQUASEAL liquid roof waterproofing systems.
- FEB AQUASEAL HYBAND SELF-ADHESIVE FLASHING TAPE.
- Self-adhesive sheet membranes.

FEB AQUASEAL FLASHING AND ROOF PRIMER may be applied to damp or dry surfaces and is suitable for application to a variety of surfaces.

FEB AQUASEAL FLASHING AND ROOF PRIMER dries rapidly and may impart a degree of waterproofing until further work is carried out.

Features & Benefits

- Early resistance to rain.
- Multi-use product.
- Simple brush application.

Instructions for Use

Preparation of Substrate

Surfaces on to which FEB AQUASEAL FLASHING AND ROOF PRIMER is applied must be clean, and free from dirt, grease or other material, which may impair adhesion. Where there is moss or lichen present, clean surfaces with EVERBUILD MOSSAWAY as directed, before proceeding.

Application

FEB AQUASEAL FLASHING AND ROOF PRIMER can be applied by brush to damp (not wet) or dry surfaces. FEB AQUASEAL FLASHING AND ROOF PRIMER dries quickly and is resistant to rainfall 20 – 30 minutes after application.

Coverage

The generally recommended coverage rate for FEB AQUASEAL FLASHING AND ROOF PRIMER is: Metal Surfaces 12 – 16m²/ltr Porous Surfaces 6 – 8m²/ltr Tools and equipment may be cleaned using white spirit or paraffin.

Storage

FEB AQUASEAL FLASHING AND ROOF PRIMER contains a flammable solvent and all precautions against fire must be taken during both storage and use. Store in cool conditions. Keep away from sources of ignition. No Smoking. Refer to Health and Safety data sheet.

Shelf Life

Minimum two years when stored in unopened containers according to the manufacturer's instructions.

