

Technical Specification/ Product Datasheet

Clark-Drain Ltd.,
Station Road,
Yaxley,
Peterborough,
PE7 3EQ.
England.



Specific Product Code/s:	CD 1659 KMD (100mm deep) CD 1659A KMD (150mm deep, pictured)	
Product Group:	Ductile Iron Kitemark Manhole Covers	
Sub-Category:	D400 Double-Tri Manhole Covers for non-carriageway use	
Material Grade/s:	Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2011 Temporary Bitumen-based paint coating to BS 3416:1991	
Basic Dimensions (mm):	CD 1659 KMD	CD 1659A KMD
Clear Opening =	675 x 675	675 x 675
Overall Size =	813 x 813	821 x 821
Depth =	100	150
Weight (kgs):	Overall = 76 Covers (per pair) = 53	85 53
Frame Pressure Bearing Area (N/mm ²):	2.8	2.75
Polished Skid-Resistance Value (PSRV):	45+	
Load Rating Classification:	D400 (40 tonnes)	
Features:	<ul style="list-style-type: none"> - BSI Kitemark Certified to BS EN124:1994 (copy certificate available upon request) - Non-rock 3 point suspension covers - Integral lifting key holes (to suit CD 552 lifting keys, available separately) - Available as a locking versions - Optional "FW" or "SW" badging - Available with optional Skid-Resistant coating on top surface (ask for details) 	

Date Issued: 05/01/16