

## Technical Specification/ Product Datasheet

Clark-Drain Ltd., Station Road, Yaxley, Peterborough, PE7 3EQ. England.

Specific Product Code/s: CD 180 KMDL

Product Group: Ductile Iron Kitemark Gully Grates & Frames

Sub-Category: D400 Hinged Gully Grates & Frames for use in carriageway

kerbside areas and commercial/industrial areas

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7

to BS EN 1563:2011

Temporary Bitumen-based paint coating to BS 3416:1991

Basic Dimensions (mm): Clear Opening =  $430 \times 370$ 

Overall size =  $570 \times 459$ 

Depth = 100

Weight (kgs): 30

Frame Pressure

Bearing Area (N/mm<sup>2</sup>): 4.79

Waterway Area (cm<sup>2</sup>): 994

Load Rating Classification: D400 (40 tonnes)

Features: - BSI Kitemark Certified to BS EN124:1994

Captive hinge design to deter thieves

3-Sided Flange for installation against kerbs

- "Taper-Lock" grating design to ensure non-rocking

- Integral lever point to aid opening

 Compliant to the design requirements of the UK Highways Agency DMRB HA104/09 for Gully Tops

- Supplied with M8 cap-head locking bolt

Cappiled with the cap fledd leoking box

Date Issued: 10/04/17

