


Technical Specification/ Product Datasheet

Clark-Drain Ltd.,
 Station Road,
 Yaxley,
 Peterborough,
 PE7 3EQ.
 England.



Specific Product Code/s: **CLKS 231 KMD**

Product Group: Ductile Iron Kitemark Gully Grates & Frames

Sub-Category: D400 Hinged Gully Grates & Frames for use in carriageway kerbside areas and commercial/industrial areas subject to pedestrian traffic in addition to road vehicles

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2011
 Temporary Bitumen-based paint coating to BS 3416:1991

Basic Dimensions (mm): Clear Opening = 430 x 370
 Overall size = 580 x 463
 Depth = 100

Weight (kgs): 30

Frame Pressure
 Bearing Area (N/mm²): 4.45

Waterway Area (cm²): 818

Load Rating Classification: D400 (40 tonnes)

- Features:
- BSI Kitemark Certified to BS EN124:1994 (copy certificate available upon request)
 - "Taper-Lock" grating design to ensure non-rock
 - Captive hinge to deter thieves
 - Mesh grating for use in pedestrian areas
 - Reduced height frame webs to aid fitting in block-paved areas

Date Issued: 15/04/15