

# TECHNICAL DATA SHEET

## CROMAPOL CLEAR

Issue 2 – December 2011

**Description:**

Cromapol Clear is a one-component, fibre free, UV stable, solvent based multi-purpose roof coating membrane. This product is not suitable for use on roof tiles.

**Waterproof Protection of:**

Flat Roofs, Corrugated Asbestos, Roof Lights, Flashings, Roofing Felt, Gutters, Asphalt, Lead, Glasshouses, Metal and Fibreglass.

**Colour:**

Clear

**Coverage Rates:**

1 - 2 kg per m<sup>2</sup> on average.

**Drying Time:**

Up to 72 hours dependent on the ambient temperature.

**Container Sizes:**

5 & 20 kg

**Shelf Life:**

12 months

**Flashpoint:**

40°C

**VOC Details:**

EU Limit for this product CAT. 2(i) : 500g/l (2010). This product contains max. 459 g/l VOC's

**Storage:**

Store away from children, preferable undercover and between 5°C - 20°C

**Surface Preparation:**

Whilst minimal preparations are required, the surface must be sound and free of loose or friable materials.

To obtain the best result remove all surface debris and surface water using a stiff broom and power wash.

Fungus, mould and lichens must be removed, additional protection against fungal spores can be achieved by applying Moss & Mould Remover.

Oil or grease must be removed prior to application.

Any existing coating must be inspected and adhesion test carried out.

**Application:**

Cromapol Clear is easily applied by a brush or roller. Treat all details first, in areas where excessive movement may occur additional reinforcement can be incorporated into the coating. Cromapol Clear can be applied in one coat, but experience has shown that a two coat application ensure a greater uniformity of coating thickness. Cromapol Clear requires no primer on most surfaces. It is therefore good practice to carry out adhesive test prior to application of the coating. Cromapol Clear will tolerate damp surfaces although with any application for best result apply to a dry surface if possible. Product may appear milky/patchy until fully cured.

Application temperature should be between 5°C - 25°C

**EXTERNAL USE ONLY****Health & Safety:**

Please refer to health & safety data sheet on Cromapol Clear.

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com) or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)