
DuPont™ Typar®SF24


Mini Pack 4.5 m x 11.1 m

The Professional Geotextile





Building, Construction & Filtration Geotextile















- Perfect stabiliser
- Perfect filter
- ✓ Easy to install
- ✓ Easy to handle/cut
- Saves aggregate
- Can be covered with many different materials (paving slabs, washed gavels, sand,...)

DuPont™ Typar® SF is a high tensile strength, nonwoven geotextile, made from uniquely-bonded polypropylene filaments. DuPont™ Typar® SF is designed to allow water through whilst separating and stabilising construction layers.

For ground drains DuPont™ Typar® SF is used as a filter membrane, helping to prevent soil or sand from clogging drainage stone.

DuPont™ Typar® SF is easy to cut. Overlap by 30cm (12") if required. When preparing the ground for laying remove all large stones and other material which may damage the fabric and level the area to remove any undulations and ruts.

When selecting the aggregate use chippings, gravel, pebbles, crushed stone etc. Make sure that the mix consists of varying sizes of stone including small material that can be compacted to give a stable surface.

To provide support for vehicles the depth of aggregate should be between 30 - 40cm (12 - 16") after compaction.

To protect DuPont™ Typar® SF whilst laying, place the aggregate on the material and spread to a depth that will allow for compaction. Avoid using the surface for access until aggregate is compacted.

Product safety information is available upon request. This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own experimentation. It is not intended, however, to substitude for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

> DuPont de Nemours (Luxembourg) S.à r.l. rue Général Patton L - 2984 Luxembourg Tel: +352 3666 5779 Fax: +352 3666 5021

www.typargeo.com

Nominal unit gross weight 4kg Nominal unit weight of material 80g/m



